

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.


**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

REMARKS

This Preliminary Amendment cancels claims elected in the parent application, U.S. Patent Application No. 10/011,638. Claims 44-61 are pending. An Action on the merits is requested at the earliest opportunity.

Respectfully submitted,

Date: February 23, 2004



Michael A. Sartori, Ph.D.

Registration No. 41,289

VENABLE LPP

P.O. Box 34385

Washington, D.C. 20043-9998

Telephone: (202) 344-4000

Telefax: (202) 344-8300

MAS/mg
PC Docs No. 524955

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of:

Shiro SUYAM et al.

Divisional of Appl. No.: 10/011,638

Confirmation No.: To Be Assigned

Filed: February 23, 2004

For: Optical Device And Three-
Dimensional Display Device

Art Unit: To Be Assigned

Examiner: To Be Assigned

Atty. Docket No.: 32307-201092

Customer No.: **26694**

Marked-Up Copy of Specification

Commissioner for Patents
P.O. Box 1450
Alexandria, VA. 22313-1450

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to an optical device which can periodically or sequentially vary ^{an} optical property ^{of} in the optical device, such as ^{the} a focal length of a lens, ^{the} a deflection angle of a prism, ^{the} a divergence angle of a lenticular lens and
10 so on.

 Further, the present invention relates to a three-dimensional display device and its driving method. More specifically, the present invention relates to a technology effectively applicable to an
15 apparatus for displaying a two-dimensional image to be displayed on a two-dimensional display device in a three-dimensional fashion.

Description of the Related Art

20 Most of the conventional optical devices are passive optical devices. ^{the kinds} ~~Kinds~~ of active optical devices whose optical properties can be varied by voltage or the like are quite limited. ^{Amongst them,} ~~Amongst,~~ ^a as
25 an optical device employing a material having ^a variable refractive index, there is a liquid crystal

lens disclosed in Science Research Expenditure
Subsidy Research Results Report No. 59850048 (1984).

Fig. 1 shows a^{pr} construction of such a liquid
crystal lens. The liquid crystal lens having
5 optical properties to be varied by voltage or the
like shown in Fig. 1 is constructed with a planar
convex lens 1 formed of a polymer, glass or the
like, a transparent electrode formed on the surface
of the planar concave lens 1, an alignment layer
10 formed of a polyimide or the like on the transparent
electrode 2, a liquid crystal 4 (ordinary nematic
liquid crystal having an anisotropy of^{1/3} dielectric
constant which is not reversed by difference of
frequency), an opposite substrate 5 opposite to
15 these components, a transparent electrode 6 formed
on the opposite substrate 5, an alignment layer 7
formed of polyimide or the like on the transparent
electrode 6, and a driving device for driving these
components. Here, the alignment layers 3 and 7 are
20 in^a homogeneous alignment condition for aligning the
liquid crystal 4 ~~in~~ substantiallyⁱⁿ parallel.

In the condition where no voltage is applied
between the transparent electrodes 2 and 6, the
liquid crystal 4 is aligned to be substantially
25 parallel to the alignment layers 3 and 7 by the
action of the alignment layers 3 and 7. In this

case, an incident light beam 11 in ^{that is} ~~a~~ polarized condition to be parallel to the alignment direction is subject to an extraordinary refractive index of the liquid crystal 4. Thus, for example, the liquid
5 crystal 4 appears to have a large refractive index in comparison with the planar concave lens 1 so that the entire optical device serves as ^a ~~the~~ planar convex lens to cause convergence as an output light beam 12.

10 On the other hand, in the condition where an appropriate voltage is applied between the transparent electrodes 2 and 6, the liquid crystal 4 is aligned to be perpendicular to the electrode 2 and 6. In this case, the incident light beam 11 is
15 subject to the ordinary refraction of the liquid crystal 4. Therefore, for example, the liquid crystal 4 appears to have substantially the same refractive index as the planar concave lens. Then, the entire optical device merely serves as glass
20 plate to output a light beam 13 having substantially the same direction as the incident light beam 11.

Even in such a conventional optical device, it has been possible to sequentially vary an optical property, e.g. focal length, of the planar convex
25 lens depending upon an applied voltage. One example of this relationship is illustrated in Fig. 2.

However, the conventional optical device has the following defects. Alignment of the liquid crystal 4 in the condition where no voltage is applied, is performed only by ^{an}anchoring force of the alignment layers 3 and 7. In such an optical device, since the liquid crystal 4 has a large thickness of several hundreds μm or more, a drawback has been encountered in that a resumption timing upon driving is delayed significantly by several seconds, as shown in Fig. 3. Furthermore, even if the applied voltage is increased, the resumption timing can be hardly improved. Therefore, currently, there is no effective method for shortening a resumption period.

As set forth above, when the liquid crystal 4 is aligned only by ^{the}anchoring force of the alignment layers 3 and 7, molecules 4a of the liquid crystal 4 may be aligned along a curved surface of the planar concave lens in a portion located in the vicinity of the transparent electrode 2, as shown in Fig. 4. Therefore, alignment of a part of the liquid crystal tends to be inclined, so that the refractive index to be sensed by the incident light beam becomes closer to the refractive index of the planar concave lens, thereby making ^{the amount of} a variation amount of the optical property smaller. Furthermore, there is a disadvantage ⁱⁿ that distribution of the variation

amount of the optical property depending on the ^{defocus} position ^{with respect to} of the lens ~~is caused~~.

ended
corrections →

Further, since the transparent electrode 2 is formed on the surface of the planar concave lens 1, when the voltage is applied, an electric field perpendicular to its surface is established in the vicinity of the transparent electrode 2 so that the liquid crystal 4 may be aligned perpendicularly to the surface thereof. As a result, there arises an inclination of ^{the} alignment of a part of the liquid crystal 4 to form a region where the refractive index sensed by the incident light beam is significantly different from the refractive index of the planar concave lens 1. Thus, the incident light beam which should pass through without any deflection substantially, is locally deflected.

Furthermore, in the case where the surface configuration of the planar concave lens 1 is more complicated, particularly when it has deep grooves or sharp projections, it becomes difficult to uniformly form the transparent electrode, so that a circuit breakage or high resistance is liable to occur.

Additionally, in such case, an alignment process of the alignment layers for aligning the liquid crystal, such as ^arubbing process and the like,

becomes difficult. Further, ^{the} distance between the transparent electrodes varies according to ^{at different} positions as ^{is} clear from Fig. 1. Despite this fact, since ^{an} the equal voltage is applied to ^{all} entire positions of the transparent electrodes, degradation of insulation, short circuit, ^{circuits,} etc. are liable to occur in a narrow region.

As set forth above, the conventional active optical device employing ^a the material having a variable refractive index encounters various practical drawbacks or shortcoming in production and ^{driving.} ~~driving, such as in long resumption period, non-uniformity.~~

15 SUMMARY OF THE INVENTION

It is an object of the present invention to provide an optical device which can be driven at high speed, achieves high uniformity, is easy to fabricate, and can vary ^{an} optical property sequentially, periodically in an active manner.

According to the present invention, there is an optical device comprising:

a transparent material layer having a desired curved surface configuration;

a layer including a variable refractive index material having a dielectric constant anisotropy and having a property in which a sign of a difference $\Delta\epsilon$ in dielectric constant due to the anisotropy is
5 reversed at driving frequencies f_1 and f_2 ;

at least two transparent electrodes arranged to sandwich the transparent material layer and the layer including the variable refractive index material; and

10 a driving device supplying a voltage including the driving frequencies f_1 and f_2 between the transparent electrodes.

The optical device according to the invention enables ~~a~~ high speed operation by varying ^{the} refractive index by varying ^{the} frequency of a voltage to be ^{which is} applied to the variable refractive index material, ^{in order} to vary ^{on} the optical property of the device, ~~formed together with the transparent material having the desired curved surface configuration.~~ Furthermore,
15 since the force of the electric field can be always used, the speed can be made higher by increasing the electric field.
20

In addition, in the optical device according to the invention, the force of the electric field can
25 be varied by the variable refractive index material, and since the transparent electrodes are not

provided on the side of the variable refractive index material of the transparent material layer, the optical device is hardly influenced by the surface configuration of the transparent material layer, compared to the prior art device, regardless of the condition of the variable refractive index material, ~~and~~ ^{the} therefore an amount of variation of the optical property can be easily ^{made} uniform. Since the transparent electrodes are not provided on the side of the variable refractive index material of the transparent material layer in the optical device according to the present invention, it becomes unnecessary to form ^a ~~the~~ film to meet the shape of the complicated surface configuration to facilitate fabrication of the optical device, compared to the prior art device. Furthermore, since the transparent electrodes are not provided on the side of the variable refractive index material of the transparent material layer, the distance between the transparent electrodes can be maintained substantially the same, and the transparent material layer is always present between the transparent electrodes, degradation of insulation, ^{short} ~~short~~ and so on hardly occur.

Further, by replacing one of the transparent ~~electrode~~ ^{electrodes} with an electrode reflecting at least a

part of the incident light beam, an active mirror, half mirror or ~~other~~^{other} various types of optical devices for varying^{an} optical property can be realized.

5 According to the present invention, there is an optical device comprising:

a layer including a variable refractive index material having dielectric constant anisotropy and having a property to reverse signs of a difference
10 of dielectric constant $\Delta\epsilon$ due to anisotropy at driving frequencies f_1 and f_2 ;

at least two transparent electrodes arranged to sandwich the layer including the variable refractive index material; and

15 a driving device applying a voltage, in which voltages from V_1 to V_N respectively having respective primary frequencies f_1 to f_N ($N \geq 2$) are superimposed, between the transparent electrodes.

According to the present invention, there is an
20 optical device comprising:

a layer of transparent material having a desired curved surface configuration;

a layer including a variable refractive index material having a positive or negative dielectric
25 constant anisotropy;

at least two transparent electrodes arranged to sandwich the layer of the transparent material and the layer including the variable refractive index material; and

- 5 a driving device for always supplying a voltage substantially equal to or greater than an amplitude of a voltage establishing static and vertical alignment in the variable refractive index material.

As set forth above, the optical device according
10 to the present invention has ^athe driving device which can always supply the voltage having an amplitude equal to or greater than the voltage, at which the variable refractive index material is statistically aligned to generate electrofluid
15 motion in the molecules of the liquid crystal to change the refractive index of the variable refractive index material in such a way that the orientation of the liquid crystal molecules vary in synchronism with a frequency twice ^{that} of the frequency
20 of the voltage applied ^{between} the state where the orientations of the liquid crystal molecules is perpendicular or parallel to the electrode and the state where the orientation of the liquid crystal molecules is slightly inclined from the former
25 state. Therefore, the optical device according to the present invention can vary the optical property

at a high speed, sequentially, periodically and uniformly. Furthermore, it becomes unnecessary to process the film to meet ^athe complicated surface configuration, ^{and} the fabrication can be facilitated.

5. According to the present invention, there is a three-dimensional display device for forming ^athree-dimensional image from two-dimensional image ^{on a}display portion, comprising:

10 a layer of a transparent material having a desired curved surface configuration;

a layer of a variable refractive index material having a refractive index varying in accordance with a voltage applied thereto;

15 at least two transparent electrodes arranged to sandwich the layer of the transparent material and the layer including the variable refractive index material;

20 an imaging position shifting portion for shifting an imaging position of the two-dimensional image displayed on the display portion;

a synchronizing portion for synchronizing an updating period of the two-dimensional image displayed on the display portion with a shifting period of the imaging point of the imaging position
25 shifting portion; and

a driving portion for driving the imaging point shifting portion by applying a voltage to the at least two transparent electrodes in accordance with an output from the synchronizing portion. ~~The~~
5 ^{P. The} three-dimensional display device according to the present invention decomposes the three-dimensional image into two-dimensional images (depth sample images) belonging to planes set at a predetermined interval in a depth direction of an image pick-up
10 position for displaying the images in a predetermined sequence on the display portion, and the imaging position of the image to be displayed on the display portion is varied by the imaging portion shifting portion. Here, the image displayed on the
15 display portion and the imaging position are synchronized by the synchronizing portion so that the observer may view the image displayed on the display portion as a three-dimensional image.

According to the present invention, there is a
20 driving method of driving a three-dimensional display device including a display portion for displaying two-dimensional images, an imaging point shifting portion disposed between the display portion and an observer, a synchronizing portion for
25 synchronizing an updating period of the two-dimensional images displayed on the display portion

with a shifting period of the imaging point of the
imaging point shifting portion, and a driving
portion for driving the imaging point shifting
portion, the a driving method comprising the steps
5 of:

outputting a plurality of driving signals of an
output voltage V_N ($N \geq 2$) having frequency f_N as a
primary frequency for a predetermined period of time
assigned to each of the driving signals in a
10 predetermined sequence to drive the imaging point
shifting portion in the driving portion; and

updating and displaying the two-dimensional
images in a predetermined sequence on the display
portion in the synchronizing portion.

15 According to the present invention, there is a
driving method of driving a three-dimensional
display device including a display portion for
displaying two-dimensional images, an imaging point
shifting portion disposed between the display
20 portion and an observer, a synchronizing portion for
synchronizing an updating period of the two-
dimensional images displayed on the display portion
with a shifting period of the imaging point of the
imaging point shifting portion, and a driving
25 portion for driving the imaging point shifting

portion, the a driving method comprising the steps of:

in the driving portion:

generating a driving signal of a predetermined
5 output voltage in which a frequency f_N ($N \geq 2$) is superimposed;

applying the driving signal to the imaging position shifting portion;

varying the output voltage in a predetermined
10 sequence in accordance with a synchronization signal of the synchronizing portion; and

in the synchronization portion:

outputting a synchronization signal in the synchronization portion when updating two-
15 dimensional images to be displayed on the display portion.

In the foregoing three-dimensional display device, there appears a phantom image of the image on the back side or inside which should be hidden.
20 Therefore, it can be useful only for reproducing a wire frame like three-dimensional image, in practice. The invention makes it possible to display the real three-dimensional image display in this case.

25 According to the present invention, there is a three-dimensional display device comprising:

a phantom three-dimensional display device for displaying a phantom three-dimensional image; and
a shutter device formed by a shutter element for controlling a light transmittance, the shutter
5 device being located at a position where the phantom three-dimensional image is reproduced or a position optically equivalent to the position. According to the three-dimensional display device, the shutter element of the shutter device, interputs the
10 incident light beam or scatters the light beam while the phantom image on the back side as viewed from the observer is being reproduced. By this display device, many of the visual cues to depth perception can be satisfied and the natural three-dimensional
15 image with no phantom phenomenon can be reproduced in the form of motion picture.

According to the present invention, there is a three-dimensional display device comprising:

a phantom three-dimensional display device for
20 displaying a phantom three-dimensional image; and
a shutter device formed by a shutter element for controlling a light transmittance,
the phantom three-dimensional image being a real image, and the shutter element being a photoreactive
25 element for lowering a light transmittance in a real image region at the position of the shutter element

in accordance with an imaging light beam of the real image.

According to the present invention, there is a head-mount display device comprising:

5 two display devices corresponding to left and right eyes and each including a two-dimensional display device and an optical device having a variable focal length; and

a control device for controlling the two-
10 dimensional display device and the optical device having a variable focal length,

the display devices being mounted to left and right eyes, and the control device synchronously driving the two-dimensional display device and the
15 optical device to perform three-dimensional display.

The head-mount display device according to the present invention is worn on respective left and right eyes of the human being so that the human being or viewer can view display images on the two-
20 dimensional display devices through the optical device of variable focal length. Then, by varying the focal length of the optical device, the virtual image position of the display image of the two-dimensional display device is varied in the depth
25 direction. According to this display device, visual cues to depth perception, such as binocular

disparity, convergence, ^{and} focus of ^{the eyes} eye in stereoscopy can be satisfied with no discrepancy and the natural three-dimensional image with no phantom phenomenon can be reproduced at a high speed.

5

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood more fully from the detailed description given herebelow and from the accompanying drawings of the preferred
10 embodiment of the invention, which, however, should not be taken to be eliminative to the present invention, but are for explanation and understanding only.

15 In the drawings:

Fig. 1 is an illustration showing ^{the} construction of one example of ^a the conventional liquid crystal lens;

20 ^{the} Fig. 2 is a chart showing ^{the} relationship between focal length and an applied voltage in the device of Fig. 1;

Fig. 3 is a chart showing ^{the} relationship between a reaction period and an applied voltage in the device of Fig. 1;

25 Fig. 4 is a conceptual illustration showing ^{the} alignment of liquid crystal molecules by an

anchoring force of an alignment layer in the device of Fig. 1;

Fig. 5 is a conceptual illustration of alignment of the liquid crystal molecules upon charging of voltage in the device of Fig. 1;

Fig. 6 is an illustration showing ^{the} a construction of the first embodiment of an optical device according to the present invention;

Fig. 7 is a chart showing ^{the} a relationship between ^{the} a dielectric constant of ^{the} a liquid crystal of Fig. 6 and ^{the} a frequency of a driving voltage;

Fig. 8 is ~~a waveform of a~~ ^{illustrates suitable waveforms for} driving voltage of the ^{the} optical device of Fig. 6;

Fig. 9 is an explanatory illustration showing sequential periodic motion of the liquid crystal of Fig. 6;

Fig. 10 is a graph showing a plane distribution of brightness of ^{an} a output light beam;

Figs. 11A and 11B are charts illustrating ^{other waveforms for the} a ~~waveform of another~~ driving voltage of Fig. 6;

Fig. 12 is an illustration showing a matrix apparatus employing the optical device according to the present invention;

Fig. 13 is an illustration showing ^{a modification of the} an ~~embodiment~~ ^{first} of the optical device of the present invention;

Fig. 14 is an illustration showing ~~an~~ ^{another modification of} embodiment ^{the first} of the optical device of the present invention;

Fig. 15 is an illustration showing ~~an~~ ^{another modification of} embodiment ^{the first} of the optical device of the present invention;

5 Fig. 16 is an illustration showing ~~an~~ ^{another modification of} embodiment ^{the first} of the optical device of the present invention;

Fig. 17 is an illustration showing ~~an~~ ^{another modification of} embodiment ^{the first} of the optical device of the present invention;

10 Fig. 18 is an illustration showing ~~an~~ ^{another modification of} embodiment ^{the first} of the optical device of the present invention;

Fig. 19 is an illustration showing the second embodiment of the optical device according to the present invention;

15 Fig. 20 is an illustration showing a construction employing the optical device of Fig. 19;

Fig. 21 is an illustration showing the third embodiment of the optical device according to the present invention;

20 Fig. 22 is ~~a waveform of a~~ ^{illustrates suitable waveforms for the} driving voltage ~~in~~ ^{for} the device of Figs. 13-19 and Fig. 21;

Fig. 23 is ~~a waveform of~~ ^{illustrates suitable waveforms for} another driving voltage ~~in~~ ^{for} the device of Figs. 13-19 and Fig. 21;

25 Fig. 24 is an illustration showing ~~another~~ ^{a modification of} construction of the third embodiment of the present invention;

Fig. 25 is an explanatory illustration showing sequential variations of an optical property in the third embodiment of the optical device according to the present invention;

5 Figs. 26A and 26B are waveforms of a driving voltage for explaining the third embodiment of the optical device according to the present invention;

Fig. 27 is an illustration showing the fourth embodiment of the optical device according to the
10 present invention;

Fig. 28 is an illustration showing ^{a modification} ~~another~~ construction of the fourth embodiment of the optical device according to the present invention;

Fig. 29 is an illustration showing ~~a further~~ ^{another modification} construction of the fourth embodiment of the optical
15 device according to the present invention;

Fig. 30 is a chart showing ~~a~~ ^{the} relationship between ~~an applied voltage of a~~ ^{the} driving voltage for the optical device and ~~a~~ ^{the} deflection angle;

20 Fig. 31 is a chart illustrating ~~a~~ ^{the} relationship between the applied voltage and the deflection angle for explaining another driving method of the optical device according to the present invention;

Figs. 32A and 32B are charts illustrating a
25 detailed relationship between the applied voltage and the deflection angle of Fig. 31;

Figs. 33 to 37 are charts illustrating other relationships between the applied voltage and the deflection angle;

Fig. 38 is a block diagram, ^{schematically} ~~the~~ showing a ~~schematic~~ construction of a three-dimensional display device employing ~~the~~ conventional liquid crystal shutter eyeglasses;

Fig. 39 is a block diagram, ^{schematically} ~~the~~ showing a ~~schematic~~ construction of ^a ~~the~~ three-dimensional display device employing ^a ~~the~~ conventional lenticular lens sheet;

Fig. 40 is a block diagram, ^{schematically} ~~the~~ showing a ~~schematic~~ construction of a first embodiment of a three-dimensional display device according to the present invention;

Fig. 41 is a graph illustrating how ~~a~~ focal length varies when a varifocal lens is driven by ~~a~~ ^{the} driving device of the first embodiment of the three-dimensional display device according to the present invention;

Figs. 42A and 42B are views for explaining ^{the operation} operations of the first embodiment of the three-dimensional display device;

Fig. 43 is a block diagram, ^{schematically} ~~the~~ showing a ~~schematic~~ construction of a second embodiment of the three-dimensional display device according to the present invention;

Fig. 44 is an illustration for explaining the second embodiment of the three-dimensional display device;

Fig. 45 is a block diagram, ^{schematically} illustrating a ^{the} schematic construction of a third embodiment of the three-dimensional display device according to the invention;

Fig. 46 is a view, ^{schematically} showing ^{the} a schematic construction of a varifocal lens of the three-dimensional display device;

Fig. 47 is a view, ^{schematically} showing ^{the} a schematic construction of another embodiment of the three-dimensional display device;

Fig. 48 is an illustration showing a motion speed of an image by the varifocal lens;

Fig. 49 is a view, ^{schematically} showing ^{the} a schematic construction of a fourth embodiment of the three-dimensional display device according to the present invention;

Fig. 50 is an illustration showing ^{the} a basic operation of the fourth embodiment of the three-dimensional display device;

Fig. 51 is a view, ^{schematically} showing ^{the} a schematic construction of a fifth embodiment of the three-dimensional display device according to the present invention;

Fig. 52 is an illustration showing ^{the} a basic operation of the fifth embodiment of the three-dimensional display device;

Fig. 53 is a view ^{schematically} showing ^{the} a schematic construction of a sixth embodiment of the three-dimensional display device according to the present invention;

Fig. 54 is an illustration showing ^{the} a basic operation of the sixth embodiment of the three-dimensional display device;

Fig. 55 is a view ^{schematically} showing ^{the} a schematic construction of the sixth embodiment of the three-dimensional display device employing an optical system such as a lens or a mirror;

Figs. 56A to 58 are sections showing embodiments of shutter devices in the three-dimensional display device;

Fig. 59 is an illustration showing ^{the} a basic operation of a seventh embodiment of the three-dimensional display device;

Fig. 60 is a perspective view showing a first embodiment of a head-mount display device;

Fig. 61 is a plan view of the device of Fig. 60, on a plane including ^{the} eyes of an ~~observer~~ observer;

Figs. 62 and 63 are views showing ^{the} a basic operation of the first embodiment of the head-mount display device;

5 Fig. 64 is a graph illustrating ~~a~~ relationship between visual cues to depth perception, ~~and a~~ depth perceptively;

Fig. 65 is a graph illustrating the correspondence and allowable range of convergence- and accommodation;

10 Fig. 66 is a view ^{schematically} showing ~~a~~ schematic construction of a second embodiment of the head-mount display device; and

Fig. 67 is a view ^{schematically} showing ~~a~~ schematic construction of a modification of the second
15 embodiment of the head-mount display device.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention will be described
20 hereinafter in detail by way of the preferred embodiments of the present invention with reference to the accompanying drawings. In the following descriptions, numerous specific details are set forth in order to provide thorough understanding of
25 the present invention. It will be obvious, however, to those skilled in the art that the present

invention may be practiced without these specific details. In other instance, well-known structures are not shown in detail in order to avoid unnecessarily ^{obscuring} ~~obscure~~ the present invention.

- 5 At first, the preferred embodiments of an optical device according to the present invention will be discussed hereinafter. While the descriptions will be given hereinafter by way of embodiments mainly employing a fresnel lens
- 10 structure as a surface of a layer of a transparent material, it is evident that similar ^{effects} ~~effect~~ should be expected in the case of a convex lens, a concave lens, a prism array, a lens array, a lenticular lens, a diffraction grating or combinations thereof.
- 15 The embodiments set forth hereinafter mainly employ a liquid crystal as ^a variable refractive index material, but equivalent effects should be expected even when other material having frequency dependency in anisotropy of dielectric constant is used.
- 20 Furthermore, in the following embodiments ^{the} ~~are~~ refractive index of liquid crystal is substantially equal to that of the transparent material when the liquid crystal is aligned substantially perpendicular to a transparent electrode. However,
- 25 evidently, ^{effects} ~~the~~ similar ~~effect~~ should be expected even when the refractive index of a liquid crystal

is substantially equal to that of the transparent material when the liquid crystal is aligned ~~in~~ substantially parallel to the transparent electrode or when the liquid crystal is aligned at a given angle with the transparent electrode.

Furthermore, in the following embodiments, the refractive index of the liquid crystal is substantially greater than that of the transparent material, ^{but} it is clearly possible to expect the ^{effects} similar effect even in the case where the refractive index of the liquid crystal is substantially smaller than that of the transparent material or the case where the refractive index of the transparent material falls within a variation range of the refractive index of the liquid crystal.

(First Embodiment of ^{the} Optical device)

Fig. 6 shows one embodiment of the optical device according to the present invention. In Fig. 6, the optical device comprises a layer 21 of a transparent material having a desired curved surface configuration and formed of a transparent polymer, glass or the like, a variable refractive index material 22 formed of a transparent material or the like including a liquid crystal, a plurality of transparent electrodes 23 and 24 sandwiching the

transparent material layer 21 and a layer including the variable refractive index material 22 and formed of ITO or SnOx, and a driving device 25 for driving these molecules.

5 Here, if it is intended to provide a planar convex lens ^{with a} ~~variable in a~~ focal length (focal length is positive) as ~~one of~~ ^{the} an active optical device, and if ~~a~~ refractive index of the variable refractive index material 22 is substantially greater than the
10 refractive index of the transparent material layer 21, the variable refractive index material 22 may be formed in the shape of a convex lens. Accordingly, the surface configuration of the transparent material layer 21 on the side of the variable
15 refractive index material 22 may be formed in a concave fresnel lens shape as illustrated. Of course, when the refractive index of the variable refractive index material 22 is substantially smaller than the refractive index of the transparent
20 material layer 21, the surface configuration of the transparent material layer 21 on the variable refractive index material 22 side may be in the form of a convex fresnel lens, for example.

 In this embodiment, the variable refractive
25 index material 22 has a refractive index anisotropy and a dielectric constant anisotropy. This

embodiment uses ^{an} ~~and~~ example in which the dielectric constant anisotropy $\Delta\epsilon$ ($= \epsilon_{\parallel}$ (dielectric constant in parallel to a longer axis of the molecule) - ϵ_{\perp} (dielectric constant in a direction perpendicular to the longer axis of the molecule)) is positive at a frequency f_{11} , and the dielectric constant anisotropy $\Delta\epsilon$ is negative at a frequency f_{12} .

Further, this embodiment uses an example in which ^{the} refractive index anisotropy n_o (ordinary refractive index) is substantially equal to the refractive index of the transparent material layer 21, and n_e (extraordinary refractive index) is substantially greater than the refractive index of the transparent material layer 21.

When an electric field having a frequency f_{11} is applied between the transparent electrodes 23 and 24 from the driving device 25, $\Delta\epsilon > 0$. Consequently, the molecules of the variable refractive index material 22 are aligned in parallel to ^{the} ~~the~~ direction of the electric field, namely ^{or} ~~in~~ perpendicular to the transparent electrodes 23 and 24. Therefore, in view of ^{the} ~~the~~ relationship between the transparent material layer 21 and the variable refractive index material 22, the refractive index of the variable refractive index material 22 becomes substantially equal to the refractive index of the transparent

material layer 21. Consequently, the light beam 26 incident into the optical device passes substantially without any variation, as output light beam 27.

- 5 On the other hand, when an electric field having a frequency f_{12} is applied between the transparent electrodes 23 and 24 from the driving device 25, $\Delta\epsilon < 0$. Consequently, the elements of the variable refractive index material 22 are aligned
- 10 perpendicular to ^{the} direction of the electric field, namely parallel to the transparent electrodes 23 and 24. Therefore, in view of ^{the} relationship between the transparent material layer 21 and the variable refractive index material 22, the refractive index
- 15 of the variable refractive index material 22 becomes greater than the refractive index of the transparent material layer 21. ~~Here, a portion of~~ ^{In effect,} the variable refractive index material 22 becomes ~~in the shape of~~ a convex fresnel lens. The optical device according
- 20 to this embodiment serves as a convex fresnel lens for an incident light beam 26 as a polarized light beam parallel to the longer axis of the molecules of the variable refractive index material 22, and converges as a output light beam 28.
- 25 In this embodiment, the focal length of the lens ~~can be varied among~~ ^{is an} optical ^{property} properties of the

optical device, ^{device that can be varied} by varying the refractive index of the variable refractive index material 22.

In this embodiment, unlike the prior art shown in Figs. 1 to 5, a force exerted by the electric field 10 is mainly utilized by varying the alignment of the variable refractive index material 22 depending upon difference of the frequency of the applied voltage. Therefore, by increasing the intensity of the electric field, ^{the} a variation speed can be extremely increased.

Further, the alignment of the variable refractive index material 22 is varied by the force exerted by the electric field, and the transparent electrode 23 is not provided on the transparent material layer 21 on the side of the variable refractive index material 22. Therefore, in either alignment condition of the variable refractive index material 22, the influence of the surface configuration of the transparent material layer 21 becomes much smaller than that in the prior art shown in Figs. 1 to 5, facilitating ~~to~~ uniform ~~the~~ variation ~~amount~~ of the focal length.

Since the transparent electrode 23 is not provided on the transparent material layer 21 on the side of the variable refractive index material 22, it becomes unnecessary to form ^a the layer ^{on a} at the

portion having a complicate configuration, thus facilitating ^{the} fabrication process to a greater degree than the prior art illustrated in Figs. 1 to 5.

5 Furthermore, since the transparent electrode 23 is not provided on the transparent material layer 21 on the side of the variable refractive index material 22, it becomes easy to set the distance between the transparent electrodes 23 and 24
10 substantially equal. In addition, since the transparent material layer 21 is always present between the transparent electrodes 23 and 24, degradation of insulation, short-circuiting or the like which are liable to occur in the prior art of
15 Figs. 1 to 5, can be successfully avoided.

As set forth above, the refractive index of the transparent material layer and the ordinary refractive index (or extraordinary refractive index) of the variable refractive index material, such as
20 ~~the~~ liquid crystal or the like, are set to be substantially equal to each other, but this is not necessarily required ~~to do so~~. Namely, setting the ^{substantially equal} refractive indexing, corresponds to ^{setting} ~~set~~ the focal length close to infinite. However,
25 if it is difficult to set the refractive indexes at substantially equal values from the viewpoint of

materials, or if ~~the~~ materials which allow setting of the refractive indexes at substantially equal ^{values} ~~value~~ cannot be employed in relation with other physical ^{properties} ~~property~~ (dielectric constant anisotropy,

- 5 refractive index anisotropy, temperature characteristics, mixing ability with catalyst, toxicity and so forth), it may be possible to set the focal length close to infinite by ^a correction made by arranging other ^a fixed focus lens at ^{the} front or
10 back side of the device.

Thus, this embodiment can increase ^{the} a driving speed in comparison with the prior art, provides superior uniformity, easiness of fabrication, and thus can solve the problems in driving.

- 15 Figs. 7 to 12 shows an embodiment employing a nematic liquid crystal as one example of ~~this~~ ~~embodiment~~ of the optical device according to the present invention.

- Here, as a material showing dielectric constant
20 anisotropy depending upon ^{the} a frequency, such as ^{the} variable refractive index material employed in the present invention, there is a dual-frequency liquid crystal, ^{crystals.} among the nematic liquid crystal.

- Fig. 7 shows a specific example of ^{the} driving
25 frequency dependency of the dielectric constant anisotropy $\Delta\epsilon$ ($= \epsilon_{\parallel} - \epsilon_{\perp}$) of the dual-frequency

liquid crystal. The example of the nematic liquid crystal shown herein is $\Delta\epsilon > 0$ at a low frequency, $\Delta\epsilon$ becomes smaller gradually as the frequency becomes higher, and $\Delta\epsilon < 0$ at a high frequency range. Here, when $\Delta\epsilon > 0$, the longer axes of the molecules of the dual-frequency liquid crystal are aligned along the electric field, and when $\Delta\epsilon < 0$, the longer axes of the molecules of the dual-frequency liquid crystal are aligned perpendicularly to the electric field. Accordingly, by simply varying the frequency, the refractive index of the dual-frequency liquid crystal can be varied in a substantially binary manner (n_o and n_e), and thus the refractive index cannot be varied sequentially. (It should be noted that it may be possible to vary the refractive index by a balance of the anchoring force of the alignment layer and the force of the electric field, but this may encounter various problems as pointed out in the prior art.)

Fig. 8 illustrates one example of a waveform of the driving voltage which can periodically vary the refractive index of the dual-frequency liquid crystal sequentially. An example is shown in which two frequencies f_{11} ($\Delta\epsilon > 0$) and f_{12} ($\Delta\epsilon < 0$), at which ~~signs of the $\Delta\epsilon$ are differentiated,~~ ^{has different signs,} are used. In the driving method in this embodiment, a voltage

having a primary frequency at f_{11} and a voltage having an equal amplitude to the former voltage and having the ^aprimary frequency at f_{12} are applied at a given duty ratio and a given period.

when driven in this manner, the molecules of the dual-frequency liquid crystal sense and respond to a force for aligning the longer axes of the molecules along the electric field (upon application of the frequency f_{11}) and to a force for aligning the longer axes of the molecules perpendicular to the electric field (upon application the frequency f_{12}) periodically, alternately.

If there is ^{were} no other constraint, the liquid crystal should abruptly vary the property at a point switching between the frequencies f_{11} and f_{12} and cannot make a practical analogue operation. ^{operation would not be possible.} However, in practice, there are ^{constraints} constraints, such as viscosity, ~~constraining force as crystal of the liquid crystal~~ ^{and constraints} such constraint may balance with the periodically ^galternating force to permit uniform analogue periodic aligning motions at a high speed over a wide range.

It should be appreciated that, in this driving method, it is important to periodically apply the electric fields at f_{11} and f_{12} for a given period of time. ^{If} Therefore, even when the electric fields at

frequency f11 and frequency f12 are applied respectively ~~for~~ one time only, uniformity may be degraded or divergence ^{may be} increased to reduce ^{the} practicality ^{of the arrangement} as a varifocal lens. By periodically
5 applying the frequency f11 and the frequency f12 respectively for a given period, the foregoing balance may be established, and uniform operations ^{is} over ^a the wide range becomes possible.

Fig. 9 shows one example of periodical
10 sequential motions of the liquid crystal. Here, a prism shape is employed as the surface configuration of the transparent material layer in the device illustrated in Fig. 6.

Further, as driving frequencies, ^a the low
15 frequency f11 and the ^a high frequency f12 are used for driving ^{with} ~~like~~ ^{waveforms} a rectangular wave as shown in Fig. 8. In this case, when the liquid crystal is aligned perpendicularly to the transparent electrode, the refractive index of the liquid crystal and the
20 refractive index of the transparent material are substantially equal to each other. When the liquid crystal is aligned substantially parallel to the transparent electrode, the refractive index of the liquid crystal becomes greater than the refractive
25 index of the transparent material. In Fig. 9, ^{the} A horizontal axis represents a time ~~from a timing of~~ ^{the}

beginning of the high frequency f12 (standardized by
a repetition period of f11 and f12), and ^{the} a vertical
axis represents an output light beam variation angle
(degree) caused by a variation of the refractive

5 index.

It becomes clear from Fig. 9 that as ^{the} a phase
increases, the variation angle of the incident light
beam shows ^{behavior} behaviors close to a sinc wave and thus
can be varied analogously. Further, the repetition
10 period of two frequencies in this example is
substantially 20 ms. From this fact, the present
invention significantly increases a resumption speed
in comparison with several seconds achieved by the
prior art.

15 Fig. 10 shows ^{the} a shape of the output light beam
in the former example (instantaneous image at a
certain timing). When a circular spot light beam is
~~made incident as~~ the incident light beam, the output
light beam becomes ^{is} a ^{spot with a} similar spot shape at another
20 time point. Since a similar spot image can be
obtained at another timing, it becomes clear that
the liquid crystal is making uniform alignment
motions over a wide range.

25

(Another Driving System of Optical device)

Fig. 11 shows another example of the waveform of the driving voltage which may sequentially vary the refractive index of the liquid crystal. Similarly, as ^{was} explained with ^{reference to} Fig. 8, two frequencies f_{11} ($\Delta\epsilon < 0$) and f_{12} ($\Delta\epsilon > 0$) at which the signs of $\Delta\epsilon$ are different in Fig. 11. However, in Fig. 8, ^{the} voltages of the frequencies f_{11} and f_{12} ^{signs are used} having equal ^{have} amplitudes ^{and} are applied at a given duty ratio and interval. Here, supply of voltage is temporarily stopped at a desired phase at an intermediate timing in the interval and subsequently resumed.

When supply of the voltage is temporarily stopped, the molecules of the dual-frequency liquid crystal ^{may} stop at the ^{an} inclination corresponding to the stopped phase, and ^{maintain} maintains the inclined condition until ^{this} alignment is gradually disturbed by fluctuation due to ^{an} anchoring force of the alignment layer or temperature and so forth. A time elapses before the disturbance of the alignment occurs due to fluctuation due to ^{the} anchoring force of the alignment layer or temperature and so forth. It ~~is~~ normally takes several seconds or more. Accordingly, by resuming ^{the} supply of voltage within this time period, the disturbance of the alignment can be kept at a suppressed condition. Furthermore,

such small disturbance of the alignment can be corrected by resumption of the voltage supply for the given time period. By driving the liquid crystal in the manner set forth above, it becomes
5 necessary to regularly provide a given refresh time for correcting ^{the} disturbance, but a high speed variation of the refractive index (not necessarily periodic) can be achieved.

10 (Case in which Optical ~~devices~~ ^a are Arranged in Matrix)

Fig. 12 shows one example ~~of devices~~ ^a to which the above-described driving method is applied. Fig. 12 shows a device 32, in which a plurality of cells
15 31 are arranged in matrix form. As a driving sequence, at first, (1) after a given period of a refreshing operation (periodic operation shown in Fig. 8), (2) voltage supply for respective cells is stopped at phases respectively corresponding to the
20 desired variations of the refractive indexes of respective cells. Then, after the given period in each cell, refreshing operation is resumed. By repeating such manner of driving, the matrix device 32 formed with a plurality of cells can be driven.

25 Here, the waveform of the driving voltage is not limited to a sine wave. Needless to say, the ^a

rectangular wave or saw-tooth wave including the frequencies f_{11} and f_{12} as primary frequencies are also applicable. Further, it is also possible to make the amplitude vary periodically. Furthermore, this embodiment employs two frequencies, but a greater number of frequencies may be employed as a matter of course.

Since the electric field is the major factor for causing a change in ~~n~~ ^{n} refractive index in the driving method according to this embodiment, it becomes possible to further increase ~~n~~ ^{n} variation in the liquid crystal alignment condition by increasing the amplitude of the applied voltage. Namely, the period of variation of the refractive index in this driving method can be accelerated up to several ms to several tens ms in contrast to several (sec.) ^{seconds} in the prior art. This speed is sufficiently high even when the distance between the transparent electrodes becomes several hundreds μm in the construction shown in Fig. 6.

(modifications at the First.
(Another) ~~Embodiment~~ of the Optical ~~device~~ ^{modifications}

Figs. 13 to 18 show another ~~embodiment~~ of the optical device according to the present invention.

In these drawings, like portions as in the device shown in Fig. 6 will be represented by the same

reference numerals. Namely, reference numeral 22 denotes a variable refractive index material. Reference numerals 23 and 24 denote transparent electrodes. Reference numerals 25 and 41 denote a driving device and a transparent material layer, respectively.

As set forth above, the variable refractive index material 22 has refractive index anisotropy and dielectric constant anisotropy. The dielectric constant anisotropy is that $\Delta\epsilon > 0$ at the frequency f_{11} and $\Delta\epsilon < 0$ at the frequency f_{12} . Further, the refractive index anisotropy is that n_o (ordinary refractive index) is substantially equal to the refractive index of the transparent material layer 41, and n_e (extraordinary refractive index) is substantially greater than the refractive index of the transparent material layer 41.

In the embodiment of Figs. 13 to 18, when the dual-frequency driven liquid crystal of the pneumatic liquid crystal is employed as the variable refractive index material, ^{modifications} ~~as the driving voltage from the driving device~~ ^{may have the waveforms} those shown in Figs. 7 to 12 may be used.

In Fig. 13, the surface configuration of the transparent material layer 41 is in a convex lens shape. When the frequency f_{11} is applied, the

molecules of the variable refractive index material 22 ~~is~~^{are} aligned in parallel to the direction of the electric field, namely in a direction perpendicular to the transparent electrodes 23 and 24. Therefore, 5 in view of the relationship between the refractive index of the variable refractive index material 22 and the refractive index of the transparent material layer 41, the refractive index of the variable refractive index material 22 becomes substantially 10 equal to the refractive index of the transparent material layer 41. Accordingly, ~~the~~^{an} light beam 42 incident into this device substantially passes therethrough to be outputted as the output light beam 43 without change.

15 On the other hand, when frequency f_{12} is applied, the molecules of the variable refractive index material 22 ~~is~~^{are} aligned in the direction perpendicular to the electric field, namely in parallel to the transparent electrodes 23 and 24. 20 Therefore, based upon the relationship between the refractive index of the variable refractive index material 22 and the refractive index of the transparent material layer 41, the refractive index of the variable refractive index material 22 becomes 25 substantially greater than the refractive index of the transparent material layer 41. Here, ~~a portion~~

~~of~~ the variable refractive index material 22 becomes a concave lens. Therefore, with respect to the incident light beam 42 polarized in parallel to the longer axis of the molecules of the variable refractive index material 22 of this device, this embodiment serves as a concave lens to cause an output light beam 44.

As set forth above, in the example of Fig. 13, by varying the refractive index of the variable refractive index material 22, the focal length of the concave lens can be varied.

Fig. 14 shows a further *modification* embodiment of the optical device according to the present invention. Here is shown an example, in which a transparent material layer 45 having surface configuration in the shape of a concave lens.

When the frequency f_{11} is applied to this device, the refractive index of the variable refractive index material 22 becomes substantially equal to the refractive index of the transparent material layer 45 likewise as in the *arrangement* embodiment shown in Fig. 13. Then, the incident light beam 42 passes therethrough and outputted as the output light beam 43 with substantially no change.

On the other hand, when the frequency f_{12} is applied, the refractive index of the variable

refractive index material 22 becomes greater than the refractive index of the transparent material layer 45 as in Fig. 13. Here, since a portion of the variable refractive index material 22 is tormented into the convex lens shaped configuration, this embodiment serves as the convex lens with respect to the incident light beam polarized in parallel to the longer axis of the molecule of the variable refractive index material 22 to converge the light beam as the output light beam 46.

Thus, in the embodiment of Fig. 14, by varying the refractive index of the variable refractive index material 22, the focal length of the convex lens can be varied.

Fig. 15 shows a still further embodiment of this embodiment of the optical device according to the present invention. Here, a transparent material layer 47 having a convex fresnel lens surface configuration is employed in the embodiment of Fig. 13.

When the frequency f_{11} is applied to this device, the refractive index of the variable refractive index material 22 becomes substantially equal to the refractive index of the transparent material layer 47 likewise in Fig. 13. Then, the incident light beam 42 passes therethrough and

outputted as the output light beam 43 with substantially no change.

On the other hand, when the frequency f_{12} is applied, the refractive index of the variable refractive index material 22 becomes greater than the refractive index of the transparent material layer 47 likewise ^{as} in Fig. 13. Here, since ~~a~~ portion ~~of~~ the variable refractive index material 22 is formed into the ^a concave fresnel lens shaped configuration, this embodiment ^{arrangement} serves as the concave fresnel lens for ^{an incident} the light beam ~~inciding with a~~ deflection ~~in parallel to the longer axis of the~~ molecule of the variable refractive index material ~~22~~ ^{so} to diverge the light beam ^{to provide an} as the output light beam 48.

Thus, in the embodiment of Fig. 15, by varying the refractive index of the variable refractive index material 22, the focal length of the concave fresnel lens can be varied. ^{modification}

Fig. 16 shows a yet further embodiment of the ~~show embodiment of the~~ optical device according to the present invention. Here, a transparent material layer 49 having a prism array like surface configuration is employed in the embodiment of Fig. 13. ^{arrangement}

When the frequency f_{11} is applied to this device, the refractive index of the variable refractive index material 22 becomes substantially equal to the refractive index of the transparent material layer 49 likewise as in Fig. 13. Then, the incident light beam 42 passes therethrough and is outputted as the output light beam 43 with substantially no change.

On the other hand, when the frequency f_{12} is applied, the refractive index of the variable refractive index material 22 becomes greater than the refractive index of the transparent material layer 49 likewise as in Fig. 13. With respect to the incident light beam polarized in parallel to the longer axis of the molecule of the variable refractive index material 22, this embodiment serves as a deflection molecule for deflecting the light beam depending upon the difference in the refractive indexes and the inclination of the prism to deflect the light as the output light beam 50.

Thus, in the embodiment of Fig. 16, by varying the refractive index of the variable refractive index material 22, the deflection angle of the deflection molecule can be varied.

Fig. 17 shows a yet further embodiment of the show embodiment of the optical device according to

the present invention. Here, a transparent material layer 51 having ^a surface configuration in the shape of a concave lenticular lens is employed in the ^{arrangement} embodiment of Fig. 13.

- 5 When the frequency f11 is applied to this device, similarly to the embodiment shown in Fig. 13, the refractive index of the variable refractive index material 22 becomes substantially equal to the refractive index of the transparent material layer 10 51. Then, the incident light beam 42 passes therethrough and ^{is} outputted as the output light beam 43 with substantially no change.

- On the other hand, when the frequency f12 is applied, the refractive index of the variable refractive index material 22 becomes greater than 15 the refractive index of the transparent material layer 51 as in Fig. 13. Here, since ~~a~~ portion of ~~the~~ variable refractive index material 22 is formed into the convex lenticular lens shaped configuration, this ^{arrangement + a} embodiment serves as the convex 20 lenticular lens with respect to the incident light beam polarized in parallel to the longer axis of the molecule of the variable refractive index material 22 to diverge the light beam as ^{an} the output light 25 beam 52.

Thus, in the ^{arrangement}embodiment of Fig. 17, by varying the refractive index of the variable refractive index material 22, the focal length and diverting angle of the lenticular lens can be varied.

5 Fig. 18 shows a yet further ^{modification}embodiment of the optical device according to the present invention. Here, a transparent material layer 53 having a diffraction grating like surface configuration is employed in the ^{arrangement}embodiment of Fig. 13.

10 When the frequency f11 is applied to this device, the refractive index of the variable refractive index material 22 becomes substantially equal to the refractive index of the transparent material layer 53 as in the ^{arrangement}embodiment shown in Fig. 13. Then, the incident light beam 42 passes ^{is} therethrough and ^{is}outputted as the output light beam 43 with substantially no change.

On the other hand, when the frequency f12 is applied, the refractive index of the variable refractive index material 22 becomes greater than the refractive index of the transparent material layer 53 as in Fig. 13. Here, since ~~a portion of~~ the variable refractive index material 22 is formed into the diffraction index shaped configuration, ^{arrangement}this ^{an}embodiment serves as ~~the~~ diffraction grating with respect to the incident light beam polarized in

25

parallel to the longer axis of the ^{molecules} molecule of the variable refractive index material 22 to diffract the light beam ^{so} as ^{to provide an} ~~the~~ output light beam 54.

Thus, in the embodiment ^{arrangement} of Fig. 18, by varying
5 the refractive index of the variable refractive index material 22, a difference in the refractive index in the diffraction grating can be varied, and thus can vary the intensity of the diffracted light beam.

10

(Second Embodiment of the Optical device)

Fig. 19 shows another [≡] example of the second embodiment of the optical device according to the present invention. In the drawing, like components
15 as those in the device of Fig. 6 will be denoted by like reference numerals. Namely, reference numeral 21 denotes a transparent material layer, 22 denotes a variable refractive index material, 23 and 24 denote transparent electrodes, 25 denotes a driving
20 device, ^{and} 61 denotes an alignment layer. The alignment layer 61 is formed of polyimide, PVA, PVB, inclined evaporation deposition SiO ^{or} and so forth, and is formed on the surface of the transparent electrode 24 on the side of the variable refractive
25 index material 22. By processing the alignment layer 61 by ^{the} rubbing method or the like, the variable

refractive index material, i.e. the liquid crystal 22 in this case, can be aligned in a given direction.

By the construction and process set forth above,
5 in the driving condition where the liquid crystal 22 is aligned to be parallel to the alignment layer 61, the liquid crystal 22 can be placed in^a uniformly aligned condition in a wide domain region. Because of this, a change in the refractive index of the
10 liquid crystal 22 can efficiently propagate to the incident light beam. Further, it becomes possible to prevent diverting due to randomly orienting the molecules of liquid crystal 22 and opaquing resulting therefrom.

15 By applying the alignment layer including polyimide, FVA, PVB, inclined evaporation deposition SiO₂ and^{or} so forth on the surface of the transparent material layer 21 on the side of the liquid crystal 22, and providing the aligning process by a rubbing
20 method and the like, ^{the} alignment ability of the liquid crystal 22 on the side of the transparent material layer 21 can be improved. Further, when the transparent material layer 21 is formed by a replica method (a method for obtaining a replica of a die of
25 metal, glass, plastic or the like), it is possible to directly align the liquid in the case of a

certain direction of peeling off of the replica. In this case, since it becomes unnecessary to apply a special layer or to subject the surface having unevenness to the alignment process, fabrication of
5 this device can be facilitated.

Further, by coating a vertical alignment material on the surface of the transparent material layer 21 on the side of the liquid crystal 22, the liquid crystal 22 on the side of the transparent
10 material layer 21 can be aligned vertically. The liquid crystal 22 on the side of the transparent material layer 21 can be aligned to be oriented close to vertical by applying a material containing a group of fluorine or the like and having a low
15 wettability with the liquid crystal material on the surface of the transparent material layer 21. In such cases, it is sufficient to coat the layer. It is not required to subject ^athe surface having unevenness to the alignment process, ^{so} fabrication of
20 this device can be facilitated.

In the optical device shown in Fig. 19, as the variable refractive index material, ^athe dual-frequency liquid crystal may also be used, for example. With such structure, in the vicinity of
25 the transparent electrode, on which the alignment layer is arranged, the ^{molecules}molecule of the dual-

frequency liquid crystal (variable refractive index material) in the vicinity thereof can be aligned in a given orientation by carrying out ~~the~~^{an} alignment process such as a rubbing method or the like.

- 5 However, since no particular alignment process is applied in the vicinity of the transparent material layer, ^{the} alignment orientation of the dual-frequency liquid crystal may differ from one portion to another portion so that the variation in the refractive index cannot satisfactorily propagate to the incident light beam to make it difficult to obtain the effect of varifocal point.

- However, even in the case of such construction, by making the light beam incident from the side where the ordering of the liquid crystal has higher uniformity (e.g. side where the alignment layer is formed), this problem can be solved. Namely, by matching the polarized condition of the incident light beam with the alignment orientation, variation in the refractive index can effectively propagate to the incident light beam. This is based on the optical rotation property of the liquid crystal. When the alignment orientation of the molecules of the liquid crystal is varied toward the direction of the incident light beam at a lower speed in comparison with the wavelength, the polarizing

direction of the incident light beam is varied following a variation in the alignment orientation of the molecules of the liquid crystal. (For example, when the alignment orientation of the
5 liquid crystal is varied counterclockwise, the polarizing direction of the incident light beam is also varied counterclockwise.)

Therefore, even when the alignment orientation is made different from one position to another
10 position in the vicinity in the transparent material layer, the incident light beam may sufficiently sense the variation in the refractive index.

Such^a construction can dispense with the need to apply a special layer or the need to subject the^a
15 surface having unevenness to alignment process, thereby facilitatingⁱⁿ fabrication of this device.

Fig. 20 shows an ~~embodiment~~ of the optical device according to the invention. Namely, reference numerals 71 and 72 denote optical devices
20 having the alignment layer as discussed with respect to Fig. 19. By arranging the alignment layers in series in a manner such that they mutually intersect each other at right angles substantially, various functions can be achieved irrespective of the
25 polarizing condition of the incident light beam.

Fig. 21 shows another embodiment of the optical device according to the invention. This embodiment of the optical device comprises a variable refractive index material 81 formed of a transparent material including ~~the~~ liquid crystal, a plurality of transparent electrodes 82 and 83 sandwiching the variable refractive index material 81 and formed of ITO or SnOx, and a driving device 84 for driving these components. Here, in the embodiment of Fig. 21, there is shown one example of the active optical device which is directed to providing a device for varying a light beam phase.

In the embodiment of Fig. 21, the variable refractive index material 81 has refractive index anisotropy and dielectric constant anisotropy. ~~As~~ the dielectric constant anisotropy, $\Delta\epsilon (= \epsilon_{\parallel}$ (dielectric constant in parallel to the longer axis of the molecule) - ϵ_{\perp} (dielectric constant in an orientation perpendicular to the longer axis of the molecule)) is positive at the frequency f_{11} , ~~and~~ $\Delta\epsilon$ becomes negative at the frequency f_{12} . Further, ~~as~~ the refractive index anisotropy, n_o (ordinary refractive index) is substantially smaller than n_e (extraordinary refractive index). f_{11}

When an electric field having a frequency f_{11} is applied to the transparent electrodes 83 and 84 by

the driving device 84, $\Delta\epsilon > 0$. Thus, the molecules
of the variable refractive index material 81 ^{are} ~~is~~
aligned in a direction ^{an} parallel to the electric
field, i.e. in ~~the~~ orientation perpendicular to the
5 transparent electrodes 82 and 83. Therefore, the
refractive index of the variable refractive index
material 81 becomes n_0 , so that a phase shift
associated with the incident light beam occurs
corresponding to a product of the refractive index
10 and the thickness of the layer.

On the other hand, when the driving device 84
applies the ^{an} electric field having a frequency ^{f/2} ~~f2~~ to
the transparent electrodes 82 and 83, $\Delta\epsilon < 0$.
Consequently, the ^{molecules} molecule of the variable
15 refractive index material 81 ^{are} ~~is~~ aligned
perpendicularly to the direction of the electric
field, i.e., in parallel to the transparent
electrodes 82 and 83. Thus, the refractive index of
the variable refractive index material 81 becomes n_e
20 ~~to be~~ ^{which is} greater than that ~~in~~ n_0 . Therefore, the phase
shift of the incident light beam 85 becomes greater
in comparison with that at the frequency f31, ^{f11}.

In this embodiment described above, by varying
the refractive index of the variable refractive
25 index material 81, the phase shift of the light beam

can be varied among the optical properties of the optical device. ^{is an} ^{property}
~~device~~ ^{device that can be varied.}

(Another Driving Method ^{for an} ~~of~~ Optical device)

- 5 Figs. 22 and 23 show ~~another embodiment of the~~ ^{examples} optical device, according to the invention, illustrating an example of the driving voltage waveform which may sequentially vary the optical property. Fig. 22 illustrates a sine wave, ^{waves,} while
- 10 Fig. 23 illustrates a rectangular wave. ^{waves.} In this embodiment, ^{Fig. 22 shows} a voltage V_{SS} (in the case of the sine waves) and ^{Fig. 23 shows} a voltage V_{RR} (in case of the rectangular waves). ^{In Fig. 22,} in which a voltage V_{S1} (in the case of the sine wave) or a voltage V_{R1} (in case of the
- 15 ~~rectangular wave)~~ ^a having the frequency f_{31} as the primary frequency, and a voltage V_{S2} (in the case of the sine wave) or a voltage V_{R2} (in case of the rectangular wave) ^a having the frequency f_{32} as the primary frequency, ^{at} are superimposed ~~on~~ ^a a certain voltage ratio. ^{In Fig. 23, a voltage V_{R1} having a frequency f_{31} and a voltage V_{R2} having a frequency f_{32} are superimposed at a certain voltage ratio.}
- 20 By driving with the driving voltages as set forth above, the molecules of the liquid crystal are simultaneously subject to a force for aligning the longer axis along the electric field (upon
- 25 application of the frequency f_{31}) and a force for aligning the longer axis perpendicular to the

electric field (upon application of the frequency
f32) in a ratio corresponding to the foregoing
voltage ratio. Therefore, the molecules of the
variable refractive index material 81 are aligned to
5 be inclined from the electric field direction at an
angle where the forces in opposite directions
balance. Therefore, the refractive index can be
varied sequentially at high speed. Further, the
foregoing action may be combined with the
10 constraining force of the liquid crystal ~~as the~~
~~crystal~~ thereby to permit substantially uniform
alignment action of the liquid crystal at a high
speed over a wide domain region.

Here, the waveform of driving voltage is not
15 necessarily ~~the~~^a sine wave or rectangular wave and
may be ~~the~~^a saw-toothed wave containing the foregoing
frequencies f31 and f32 as primary frequencies.
Further, it should be clear to provide a variation
of the amplitude with time. Furthermore, two
20 frequencies are used in this embodiment, ^{but} a greater
number of frequencies may also be used.

Since the primary factor ~~to cause~~^{influencing the} refractive
index in this embodiment of the driving method is
the electric field, a higher ^{speed} speeding can be
25 achieved by increasing the amplitude. Namely, even
when the distance between the transparent electrodes

is wide, in the order of several hundreds μm , the dual-frequency liquid crystal can vary the refractive index at ~~a~~ several tens ^{of milliseconds} ms or less ~~of a~~ ^{to provide} a fast response speed.

5 Figs. 24 and 25 show one example of the foregoing driving method for the optical device. In the drawings, like components as in the device of Fig. 21 will be denoted by the like reference numerals. Namely, reference numeral 81 denotes the
10 variable refractive index material. Reference numerals 82 and 83 denote transparent electrodes. 84 denotes the driving device and 86 denotes a transparent material layer.

The transparent material layer 86 is formed of a
15 transparent polymer, glass or the like with a desired curved surface configuration and disposed between the transparent electrodes 82 and 83.

In this embodiment, as one example of the active optical device, a planar convex lens with ^a variable
20 focal length (focal length is positive) is provided. For example, when the refractive index of the variable refractive index material 81 is substantially greater than the refractive index of the transparent material layer 86, the variable
25 refractive index material 81 may be formed in the shape of a convex lens. Accordingly, the surface

configuration of the transparent material layer 86 on the side of the variable refractive index material 81 may be in the shape of a concave fresnel lens. Needless to say, if the refractive index of the variable refractive index material 81 is substantially smaller than the refractive index of the transparent material layer 86, the surface configuration of the transparent material layer 86 on the side of the variable refractive index material 81 may be in the shape of a convex fresnel lens.

In this embodiment, the variable refractive index material 81 has refractive index anisotropy and dielectric constant anisotropy. As the refractive index anisotropy, $\Delta\epsilon > 0$ at the frequency f_{31} and $\Delta\epsilon < 0$ at the frequency f_{32} . Further, in this embodiment, the dielectric constant anisotropy is such that n_o is substantially equal to the refractive index of the transparent material layer 86 and n_e is substantially greater than the refractive index of the transparent material layer 86.

When ^{an} the electric field having frequency f_{31} is applied between the transparent electrodes 82 and 83 from the driving device 84, $\Delta\epsilon > 0$. Consequently, the molecules of the variable refractive index

material 81 are aligned in parallel to the electric field, i.e. in a direction perpendicular to the transparent electrodes 82 and 83. Therefore, from the relationship between the refractive indexes of the transparent material layer 86 and the variable refractive index material 81, the refractive index of the variable refractive index material 81 becomes substantially equal to the refractive index of the transparent material layer 86. Accordingly, the light beam incident into this embodiment of the optical device according to the invention, may be outputted as an output light beam 87 with substantially no change.

On the other hand, when ^{an} the electric field having frequency f_{32} is applied between the transparent electrodes 82 and 83 from the driving device 84, $\Delta\epsilon < 0$. Consequently, the molecules of the variable refractive index material 81 are aligned perpendicular to the electric field, i.e. in parallel to the transparent electrodes 82 and 83. Therefore, from the relationship between the refractive indexes of the transparent material layer 86 and of the variable refractive index material 81, the refractive index of the variable refractive index material 81 becomes greater than the refractive index of the transparent material layer

86. Here, ~~since the portion of~~ the variable refractive index material 81 is shaped into a convex fresnel lens. This device serves as ^{an} ~~the~~ convex fresnel lens with respect to the light beam 85
5 polarized in parallel to the longer axis of the molecule to make it converge as ^{an} ~~the~~ output light beam 88.

As set forth above, in this embodiment, the total length of the lens can be varied, by varying
10 the refractive index of the variable refractive index material 81, amongst the optical properties of the optical device.

However, as set forth above, it is not possible to vary the refractive index to an intermediate
15 value between n_o and n_e by simply varying the ^{frequency} ~~frequency~~, and thus ~~optical property of the optical device, such as the focal length of the lens, cannot be varied to the intermediate value.~~

Sequential variation of the optical property of
20 the optical device can be obtained by applying the voltage V31 having the frequency f31 as ^{the} primary frequency thereof and the voltage V32 having the frequency f32 as ^{the} primary frequency thereof in a superimposing manner at a certain voltage ratio. At
25 this time, the ^{molecules} ~~molecule~~ of the dual-frequency liquid crystal ^{are} ~~is~~ aligned in an inclined orientation where

the forces in the opposite directions are balanced. Further, the constraining force of the liquid crystal ~~as the crystal~~ is combined with the action set forth above, so that uniform and high speed alignment operations of the liquid crystal become possible, thus enabling ~~to~~ ^{variation} uniformly vary the optical property.

Fig. 25 shows one example of a sequential variation in the optical property. In this example, the surface of the transparent material layer is configured in the shape of a prism. ~~A~~ ^{the} horizontal axis represents a voltage ratio ($V32/(V31 + V32)$) of the voltage $V31$ having the frequency $f31$ as the primary frequency thereof and the voltage $V32$ having the frequency $f31$ as the primary frequency thereof. The vertical axis represents a variation of the deflection angle of the output light beam with a variation in the refractive index ($V32/(V31 + V32)$). From Fig. 25, it is seen that the deflection angle of the output light beam varies ~~analogous~~ with the increase in the voltage ratio ($V32/(V31 + V32)$). It should be noted that the shape of the output light beam is similar to that of Fig. 10. From this, it becomes clear that the liquid crystal makes substantially uniform alignment actions over a wide range.

Here, the driving voltage to be applied is not necessarily the ^a sine wave. Needless to say, the ^a rectangular wave or saw-tooth wave including the frequencies f31 and f32 as primary frequencies are also applicable. Further, it is clear that the amplitude may vary with time. Furthermore, this embodiment employs two frequencies, but a greater number of frequencies may be also employed.

Since the electric field is a major factor for causing a variation in ^{the} refractive index in the driving method according to this embodiment, it becomes possible to further accelerate the speed of varying the liquid crystal alignment condition by increasing the amplitude of the applied voltage. More specifically, ^a the speed of several 10 ms or less as a response speed in the refractive index variation of the dual-frequency liquid crystal can be achieved even when the distance between the transparent electrodes reaches several hundreds μm . Furthermore, since the alignment of the variable refractive index material 81 is varied by the electric field and the transparent electrode 82 is not provided on the transparent material layer 86 on the side of the variable refractive index material 81, it becomes unnecessary to form the layer on portions of complicated configuration. Therefore,

fabrication can be facilitated in comparison with the conventional device shown in Figs. 1 to 5.

Furthermore, the transparent electrode 82 is not provided on the transparent material layer 86 on the side of the variable refractive index material 81, it ~~facilitating to make~~^{so} a substantially equal distance between the transparent electrodes 82 and 83 ~~at entire areas~~^{is maintained over the area.} Furthermore, the transparent material layer 86 essentially lies between the transparent electrodes 82 and 83, effectively preventing degradation of insulation, short circuit and so forth, unlike the device of Figs. 1 to 5. *circuits*

As set forth above, in comparison with the prior art, this embodiment can speed up driving with uniformity, can facilitate fabrication, and solve the driving problem associated with the prior art.

Fig. 26 shows a further ~~embodiment of the second~~^{modification} ~~embodiment of the optical device~~ according to the invention.

An example is given in which two frequencies f_{31} ($\Delta E > 0$) and f_{32} ($\Delta E < 0$) ~~are employed which result in~~^{are employed which result in} ΔE having different signs ~~of ΔE~~ ^a, and the dual-frequency liquid crystal is used as the variable refractive index material. Further, there ~~are~~^{waves are} the sine wave ~~is~~^{is} used in one case and the rectangular wave ~~is~~^{waves are} used in the other case.

In this embodiment of the driving method, the voltage having the frequency ^{frequency} f31 as the primary frequency and the voltage having the frequency f32 as the primary frequency are applied in a

- 5 superimposing manner at a certain voltage ratio. In addition, ~~supply of~~ the voltage is temporarily stopped at a certain timing and subsequently ^{resumed,} ~~resume~~ ~~supply of the voltage.~~

- When ~~supply of~~ the voltage is temporarily
10 stopped, the molecules of the dual frequency liquid crystal stop at the ^{an} inclination corresponding to the stopped phase, and maintain the inclined condition until alignment is gradually disturbed by fluctuation due to ^{the} anchoring force of the alignment
15 layer or temperature and so forth. A time period elapses before ^{this} disturbance of the alignment occurs due to fluctuation due to ^{the} anchoring force of the alignment layer or temperature and so forth. It ~~is~~ normally takes several seconds or more.
20 Accordingly, by ~~supply of~~ ~~resuming~~ voltage within this period, ^{the} disturbance of the alignment can be maintained as small as possible. Furthermore, such small disturbance of the alignment can be corrected by resumption of the voltage supply for a
25 predetermined interval. By driving the liquid crystal in the manner set forth above, it becomes

necessary to regularly provide a given refresh time for correcting disturbance, but a high speed variation in the refractive index can be achieved while eliminating the need to constantly apply a voltage.

This driving method is also applicable for the device in which a plurality of cells are arranged in matrix form as shown in Fig. 12. In a driving sequence, at first, (1) after a predetermined interval of refreshing operation (shown in Figs. 22 and 23), (2) voltage supply to respective cells is stopped at phases respectively corresponding to the desired variation in the refractive indexes of respective cells. Then, after the predetermined interval in each cell, refreshing operation is resumed. By repeating such driving operations, the matrix device 32 formed with a plurality of cells can be driven.

Here, the driving voltage to be applied is not necessarily ^athe sine wave. Needless to say, the ^arectangular wave or saw-tooth wave including the frequencies f_{31} and f_{32} as primary frequencies are also applicable. Further, it is also possible to provide a periodic variation in the amplitude.

Furthermore, this embodiment employs two

frequencies, ^{but} a greater number of frequencies may be employed as a matter of course.

Since the electric field is the major factor for causing the variation in the refractive index in the driving method according to this embodiment, it becomes possible to further accelerate ^{the} speed of the variation in the liquid crystal alignment condition by increasing the amplitude of the applied voltage. More specifically, the period of the variation in the refractive index in this driving method can be speeded up, exceeding several ms to several tens ms from several ^{seconds} ~~conventional~~ ^{conventional} as has been ~~convention~~. This speed is obtained when the distance between the transparent electrodes is as wide as several hundreds μm in the arrangement shown in Fig. 21. It is evident that such arrangement permits ~~the~~ sufficient speed.

The arrangements shown in Figs. 13 to 20 as described above may carry out driving operations by applying the driving voltage having the frequency F31 as the primary frequency and the voltage having the frequency F32 as the primary frequency in a superimposed manner at a certain voltage ratio as described with respect to Figs. 22, 23, and 25. Alternatively, the arrangements shown in Figs. 13 to 20 as described above may carry out driving

operations by applying the driving voltage having the frequency F31 as the primary frequency and the voltage having the frequency F32 as the primary frequency in a superimposed manner at a certain voltage ratio and, further, temporarily stopping supply of the voltage at a certain moment, followed by resuming the supply of the voltage, as described with respect to Embodiment 13.

10 (Fourth Embodiment of the Optical device)

The foregoing ^{discussions} ~~discussion~~ relate to the embodiments in which two electrodes for driving the variable refractive index material are both transparent electrodes. However, it is advantageous that one of ^{the} electrodes has a mirror surface, in some applications, for example, when an active mirror ^{an} varying ~~the~~ optical property, such as ^{the} a focal length, light beam deflection angle and so forth, is required. ~~It is also advantageous that this mirror~~
20 ^{may be} ~~uses a half mirror, as an active half mirror varying the optical property, such as a focal length, light beam deflection angle and so forth.~~

Fig. 27 shows one embodiment of the optical device according to the present invention. In the
25 drawing, like components as in Fig. 6 will be identified by like reference numerals. Reference

numeral 21 denotes the transparent material layer, 22 denotes a variable refractive index material, 23 denotes the transparent electrode, and 91 denotes an electrode.

5 The electrode 91 has a mirror surface formed in place of the transparent electrode 24 in the device of Fig. 6. The electrode 91 may be formed of metal, such as an aluminum film, chromium film or the like.

10 In the arrangement set forth above, when the frequency f_{11} is applied from a driving device, not shown, the refractive index of the variable refractive index material 22 becomes substantially equal to the refractive index of the transparent material layer 21 like~~is~~^{as} as in the first embodiment. Then, ~~the~~^{an} incident light beam 92 incident from the side of the transparent electrode 23 reaches the electrode 91 with no substantial variation, and is reflected therefrom to be outputted from the transparent electrode 23 as an
15 output light beam 93.
20

On the other hand, when the frequency f_{12} is applied, the incident light beam is subject to optical ~~effect~~^{effects}, such as, lens effect, deflection effect and the like depending upon ~~a~~^{the} variation in
25 the refractive index of the variable refractive index material 22 ~~to reach~~^{before reaching} the electrode 91, and is

reflected back therefrom to be again subject to ^athe similar optical effect to be outputted from the side of the transparent electrode 23 as an output light beam 94.

5 Thus, in the embodiment of Fig. 18, by varying the refractive index of the variable refractive index material 22, a varifocal mirror or a variable deflection angle mirror can be implemented.

Fig. 28 shows another ~~embodiment~~ ^{a modification} of the optical
10 device. In this embodiment, an electrode 95 formed ^{as} with a half mirror is used in place of the electrode 91 in the embodiment of Fig. 27. More specifically, the electrode 95 has a laminated layer of an ITO film and a metal thin film, a multi-layer film of a
15 metal thin film and an insulation film and so forth, and passes a part of the incident light beam and reflect ^{reflects the} a remaining part of the incident light beam.

In the arrangement set forth above, when the frequency f_{11} is applied from a driving device not
20 shown, the refractive index of the variable refractive index material 22 becomes substantially equal to the refractive index of the transparent material layer 21 as in the first embodiment. Then, the incident light beam 92 incident from the side of
25 the transparent electrode 23 passes through to reach the electrode 95 with no substantial variation. A

part of the light beam 95 reaching the electrode 95 passes through the electrode to be outputted as the output light beam 96a, and the remaining part of the light beam 95 is reflected back therefrom to be
5 outputted through the transparent electrode 23 as an output light beam 96b.

On the other hand, when the frequency f12 is applied, the incident light beam is subject to ^{an} optical effect, such as ^a lens effect, deflection
10 effect or the like depending upon a variation in the refractive index of the variable refractive index material 22 and reaches the electrode 95. Then, a part of the light beam passes through the electrode 95 to be outputted as an output light beam 97a, ^{and} the
15 remaining part of the light beam 95 is reflected back therefrom to be again subject to the similar optical effect to be outputted through the side of the transparent electrode 23 as an output light beam 97b.

^{modification,}
20 Thus, in this ~~embodiment~~ ^{modification}, by varying the refractive index of the variable refractive index material 22, ^a the varifocal mirror and ^a the variable deflection angle transparent optical device can be achieved simultaneously. Further, when the incident
25 light beam is made incident from the side of the electrode 95, a varifocal lens, a simple mirror and

a variable deflection angle transparent optical device can be achieved simultaneously.

Fig. 29 shows a further embodiment^{modification} of the optical device according to the invention. Here, an electrode 98 formed with^{as} a half mirror is employed in place of the transparent electrode 23 in the embodiment shown in Fig. 27. More specifically, the electrode 98 has a laminated layer of an ITO film and a metal thin film, a multi-layer film of a thin metal film and an insulation film and so forth, and passes a part of the incident light beam and reflects a remaining part of the incident light beam, like the electrode 95.

In the arrangement set forth above, when the incident light beam 92 is made incident from the side of the electrode 98, a part of the light beam is reflected back from the electrode 98 and a remaining light beam is made incident through the transparent material layer 21 and the variable refractive index material 22.

At this time, when the frequency f_{11} is applied from a deriving device not shown, the refractive index of the variable refractive index material 22 becomes substantially equal to the refractive index of the transparent material layer 21 as in the first embodiment. Then, the incident light beam 92

incident from the side of the transparent electrode 23 passes through and reaches the electrode 91 with no substantial change, and is reflected back therefrom to reach the electrode 98 again. Then, a
5 part of the reflected light beam is again reflected back from the electrode and the remaining light beam is outputted. The same process is repeated. However, in this case, since the light beam is subject to no optical effect, the output light beam
10 92 becomes ^{merely a} reflected light beam.

On the other hand, when the frequency f_{12} is applied, the incident light beam is subject to ^{an} optical effect, such as ^a lens effect, deflection effect or the like depending upon a variation in the
15 refractive index of the variable refractive index material 22 and reaches the electrode 91, and is reflected back therefrom. The reflected light beam is again subject to ^a the similar optical effect and reaches the electrode 98. Then, a part of the
20 reflected light beam is reflected back and the remaining is outputted therethrough. The foregoing process is repeated. Whenever the process is repeated, the reflected light beam is subject to the same optical effect. Therefore, the greater optical
25 effect becomes ^{as} the greater the number of ^{repetitions} repetition ^{becomes greater.}

becomes. Thus, the output light beam 99 subjected to the greater optical effect is outputted.

Thus, in this ^{modification} ~~embodiment~~ by varying the refractive index of the variable refractive index material 22, it becomes possible to provide a lens having a plurality of focal points and the variable focal points, optical devices having a plurality of deflection angles and the variable deflection angles, or the like. At this time, the number of the focal points and the deflection angles to be achieved simultaneously can be substantially determined by adjusting ^{the} ratio of passing to reflecting of the electrode 98.

15 (Another Driving Method ^{for} of the Optical device)

In the optical device shown in Fig. 6, with the increase of the frequency of the voltage ~~to be~~ applied to the electrodes 23 and 24 (the frequency thereof ^{being} ~~is~~ sufficiently higher than ^a the frequency corresponding to ^{the} response speed of the molecules of the liquid crystal, i.e. the frequency to which the ^{molecules} molecule of the liquid crystal cannot respond, e.g. several Hz to several tens Hz), the voltage reaches a level V_A at which Frederick transition takes place. At the ^a voltage higher than or equal to V_A , the ^{molecules} molecule of the liquid crystal begins to be

aligned in a perpendicular direction from the orientation in parallel to the electrode due to ^{the} dielectric constant anisotropy of the ^{molecules} molecule of the liquid crystal. By further increasing the
5 applied voltage, the molecules of the liquid crystal are statistically aligned in ^aperpendicular direction to the electrode (such given voltage is defined as VT).

Conventionally, since the liquid crystal layer
10 is driven by varying the voltage between the voltage VT and the ^a voltage lower than or equal to VA (normally 0V), the driving speed cannot be increased. In contrast, the driving method according to this embodiment can drive the liquid
15 crystal layer 22 at ^{an} increased speed by applying a voltage higher than or equal to the voltage VT.

When such high voltage is applied, the liquid crystal becomes statistically unstable to cause electrofluid dynamic motion. Because of this, the
20 molecules of the liquid crystal effectively sway between an orientation perpendicular to the electrode and an orientation slightly inclined from the perpendicular position. Such sway motions are made in synchronism with an interval of an applied
25 voltage including alternating current. It should be noted that the liquid crystal as a whole has a poor

polarizing ability, so that there is a small difference in swaying motion due to ^{the} polarity of the voltage. Therefore, the frequency of the motion of the liquid crystal becomes twice the applied
5 voltage. Further, ^{the} magnitude of the swaying motion becomes greater in proportion with ^{an} increase of the amplitude of the applied voltage. Furthermore, ^{the} relaxation time becomes significantly shorter than the static relaxation time. Therefore, the
10 refractive index of the liquid crystal layer 22 can be varied at a frequency twice the applied voltage in synchronism therewith, thus enabling speeding up.

As set forth above, with this embodiment, the optical property (such as a focal length and so
15 forth) can be varied at a high speed periodically in synchronism with the applied voltage.

Further, in this embodiment, as set forth above, since electrofluid dynamic motion can be increased by increasing the applied voltage, the effective
20 response speed can be advantageously increased. Therefore, in this embodiment, in comparison with the prior art, a higher speed operation can be achieved.

This driving method will be discussed in detail
25 with reference to the drawing.

Fig. 30 shows ^{the} behavior of the deflection angle when the amplitude of ^{the envelope of} the voltage is varied between ^{a value that is} an applied voltage higher than or equal to V_T and a ^{a value that is} voltage lower than or equal to V_T , e.g. about 0V as
5 in the prior art. As one example, as the applied voltage, a sine wave having a frequency of 30 Hz was used. The amplitude was varied in a sine-wave-like pattern. In the drawing, ^{the behavior} behaviors of the deflection angle due to the variation in the
10 amplitude of the applied voltage ^{is} are illustrated in an-envelop-like representation (i.e. fine periodic motion of the applied voltage and the deflection angle ^{are} is represented by densely ^{drawn} drawing lines).
When the liquid crystal is driven ^{such that} with lowering ^{envelope of the} the amplitude of the voltage ~~down to approximately~~ ^(approximately 0V) 0V which is equal to 0V lower than V_T , as in the prior art, there is a problem that in the vicinity of the region where the amplitude of the voltage is small, the deflection angle ^{has} makes asynchronous
20 ^{behavior} behaviors which ^{is} are clearly different from the period of the applied voltage. In the region showing asynchronous ^{behavior,} behaviors, the light beam is significantly diverted to make ^{it} difficult to definitely determine the deflection angle.
25 On the other hand, Figs. 31 and 32 show ^{the behavior} behaviors of the deflection angle in the case where

the ^{envelope of the} applied voltage is varied at the ^a voltage amplitude greater than or equal to V_T as set forth above. Fig. 31 is illustrated in the ^{an} envelope-like representation as in Fig. 30, and Fig. 32 shows
5 ^{the} detailed correspondence between the applied voltage and the deflection angle. Further, the applied voltage was in the form of the ^a sine wave having a frequency of 30 Hz, and its amplitude was varied in a-sine-wave-like pattern.

10 As ^p clear from Fig. 32; by varying the amplitude of the voltage at the voltage higher than or equal to V_T , it can be appreciated that the deflection angle can be varied at a frequency twice the
15 frequency of the applied voltage in synchronism with a period of the applied voltage. In the region where the voltage is higher than or equal to V_T , even the ^a stepwise abrupt variation in the amplitude causes no disturbance in the deflection angle substantially, following the variation of the
20 amplitude in synchronous fashion. Further, from Fig. 31, it is appreciated that the magnitude of the periodic variation in the deflection angle is variable depending upon the amplitude of the applied voltage, and no asynchronous behavior is included.

25 Furthermore, when the amplitude of the voltage higher than or equal to V_T is varied as discussed ^{previously,} in

~~the first embodiment~~, diverting of the light beam can be constantly suppressed to be low.

As set forth above, with this embodiment, high-speed response can be achieved.

5 Figs. 33 to 37 show other embodiments of this driving method. ~~In this embodiment~~, the behavior of ^{an} the optical property (e.g. deflection angle) of the optical device according to the present invention depending upon the frequency of the applied voltage
10 (amplitude $> V_T$) will be discussed. It should be noted that, as an example of the applied voltage, a sine wave is employed. Figs. 33 to 36 respectively illustrate ^{the behavior} behaviors of the deflection angle at the frequencies of the applied voltage of 0.5 Hz, 1 Hz,
15 3 Hz and 100 Hz.

The deflection angle shows ^a synchronous response even at a low frequency, i.e. 0.5 Hz, but the waveform of the deflection angle is not constant and ^{is} disturbed. The variation in ^{the} an average value in one
20 period is large. Thus, the waveform is disturbed as a whole. Furthermore, in this case, ^a large light beam diverting is caused ~~detectively~~. In contrast, in the case of 1 Hz, ^{the} disturbance of each waveform is not so large as in the case of 0.5 Hz, and ^{the} variation
25 of the average value in one period becomes smaller. In the case of 3 Hz, the disturbance becomes further

smaller. In addition, in the case of 1 Hz and 3Hz, diverting of the light beam observed in the case of 0.5 Hz, becomes extremely small. Furthermore, at the further higher frequency, such as 100 Hz, ^a neat response waveform with quite small disturbance and scattering can be obtained. Therefore, in order to restrict disturbance of the deflection angle and scattering of the light beam, it is desirable to set the frequency of the applied voltage to be higher than or equal to 1 Hz.

Fig. 37 illustrates ^{the} behavior of the deflection angle when the frequency of the applied voltage is varied in a range of 5 Hz to 100 Hz. (It should be noted that, similarly to Figs. 30 and 31, fine periodic motion of the applied voltage and the deflection angle is represented by densely ^{drawn} drawing lines). The deflection angle shows a substantially similar magnitude of variation at the frequency of the applied voltage up to about 10 Hz. When the frequency becomes higher than 10 Hz, the magnitude is gradually reduced according to ^{the} increase in frequency of the applied voltage and becomes quite small at the ^a frequency of about 100 Hz. Accordingly, from the viewpoint of ^{ensuring} ~~ensurement~~ of the magnitude of variation in ^{the} deflection angle, it is desirable to maintain the frequency of the applied

voltage to be lower than or equal to 100 Hz.

Therefore, the frequency of the applied voltage according to the present invention is practical in a range of 1 Hz to 100 Hz.

5 It should be noted that, although ⁱⁿ this embodiment, ^a the sine wave is used as the applied voltage, a similar effect can be produced even in the case of a rectangular wave, a triangular wave or ^{other} periodic other waves.

10 The above described driving method is applicable to any of the optical devices discussed above.

(Three-Dimensional Display Device Employing Optical Device)

15 ~~Discussion will be given hereinafter on a three-dimensional display device employing the~~ ^{device will now be discussed.}
~~forementioned optical device.~~

At first, a conventional three-dimensional display device will be explained. There has been
20 ^{known as} conventional ~~by known~~ three-dimensional display device, employing liquid crystal shutter eyeglasses
^{as} shown in Fig. 38. In the device shown in Fig. 38, at first, in order to obtain a so-called binocular disparity image by picking up images of a three-
25 dimensional object 51 in different directions, the image of the three-dimensional object 51 is picked

up by two cameras 52 and 53 positioned at a predetermined interval.

Then, two-dimensional images picked up by the respective cameras 52 and 53 are synthesized by an
5 image signal conversion device 54 so that the two-dimensional images picked up by the cameras 52 and 53 are arranged alternately per each field.

The image signal conversion device 54 displays the synthesized two-dimensional images on a CRT
10 display device 55, and drives a liquid crystal shutter on the left side of an observer 57 in ~~a~~ liquid crystal shutter eyeglasses 56 to be transparent and the liquid crystal shutter on the right side to be not transparent when the two-
15 dimensional image picked up by the camera 52 is displayed.

On the other hand, when the image signal conversion device 54 displays the two-dimensional image picked up by the camera 53 on the CRT display
20 device 55, the image signal conversion device 54 drives a liquid crystal shutter on the right side of the observer 57 in the liquid crystal shutter eyeglasses 56 to be transparent and the liquid crystal shutter on the left side to be not
25 transparent.

By repeating the operation set forth above, by the after image effect of the eye, the observer 57 feels as if ^{he or she is} simultaneously looking ^{at} the binocular disparity images with both eyes, to realize a three-
5 dimensional view by binocular disparity.

There has been known a three-dimensional display device not employing eyeglasses or the like, but a known lenticular lens sheet as shown in Fig. 39.

In this device, similarly to the device
10 employing the liquid crystal shutter eyeglasses, at first, the binocular disparity images of the three-dimensional object 51 are picked up by the cameras 52 and 53.

Next, respectively the image signal conversion
15 device 54 synthesizes the two two-dimensional images picked up by the cameras 52 and 53, to form a two-dimensional image in which pixels are arranged alternately in a horizontal direction.

The image signal conversion device 54 displays
20 the synthesized two-dimensional image on a matrix type two-dimensional display device 59, typified by a liquid crystal display device.

At this time, the lenticular lens sheet 58 is closely fitted to the screen of the two-dimensional
25 display device 59. Consequently, since the lenticular lens sheet 58 has directivity, the

observer can perceive, by his left and right eyes only pixels of the two-dimensional images picked up respectively by the cameras 52 and 53 according to the position of the observer 57.

5 Accordingly, the binocular disparity images picked up at a predetermined interval can be seen by both eyes of the observer 57, respectively, to thus form a three-dimensional image by the effect of binocular disparity.

10 For example, holography is known, *and can be employed to provide a* as three-dimensional display device capable of forming a more natural three-dimensional image.

In The holography *picks up* interference fringes *are picked up* when an object light beam *is* transmitted or *or* reflected light beam produced by irradiating the three-dimensional object 51 with *a* coherent light beam of high interfering performance radiated from a *coherent* light source) and a reference light beam radiated from the light beam source intersects at a *g* predetermined angle.

15
20

In the case of reproduction of a three-dimensional image, the picked-up interference fringe is read out by a light beam having a wavelength equal to that of the light beam used in picking up, to thus obtain a three-dimensional image of the three-dimensional object 51.

25

In the conventional three-dimensional display device employing the liquid crystal shutter eyeglasses, it is constantly required to wear the liquid crystal shutter eyeglasses. In the case of
5 communication such as television conferences, it becomes difficult to see the faces of attendants to
and this gives an
give awkward feeling.

In case of the three-dimensional display device employing the lenticular lens sheet, the range where
10 the binocular disparity images can be viewed by both eyes of the observer is quite limited. Therefore, the observer cannot freely select the position relative to the two-dimensional display device 59.

Moreover, since the range to be observed is
15 narrow, a plurality of people cannot observe the range at one time.

Furthermore, in the three-dimensional display device employing the liquid crystal shutter eyeglasses and the three-dimensional display device
20 employing the lenticular lens sheet, the eye of the observer is accommodated on the screen of the display device, and the accommodation is not varied according to the images to be displayed.

This may cause discrepancy between the
25 convergence perceived by the observer 57 and the

accommodated position of the eye, thus inducing asthenopia.

Further, the two-dimensional image displayed on the display device is fixed at the visual positions
5 which are, in turn, determined by the positions of the cameras 52 and 53. Therefore, it is not possible to express the movement. Even when the observer 57 moves, the image displayed on the display device looks to move together with the
10 observer. This gives the observer a sense of incompatibility.

In the three-dimensional display device employing ~~the~~ holography, a coherent light beam such as a laser beam is required in picking-up the three-
15 dimensional object. Further, the information amount to be obtained becomes huge to make it impossible to process the information of a moving picture at a ^{1/2} real time.

According to the present invention, ~~the~~ ^{the} three-
20 dimensional display device employing the aforementioned optical device can solve the problems described above. Consequently, an object of the three-dimensional display according to the present invention is to satisfy the binocular disparity,
25 convergence and accommodation and movement parallax as visual cues to depth perception in three-

dimensional view⁵ without employing eyeglasses or the like, and to achieve moving picture displaying which can be re-written electrically.

Further, it is another object of the present
5 invention to provide a driving method for driving the three-dimensional display device which can satisfy the binocular disparity, convergence and accommodation and movement parallax as visual cues to depth perception in three-dimensional view
10 without employing the eyeglasses or the like, and can achieve moving picture displaying which can be re-written electrically.

Preferred embodiments of the three-dimensional display device according to the present invention
15 will be described hereinafter in detail with reference to the accompanying drawings.

Like molecules or corresponding parts having like functions will be designated by the same reference numerals throughout the all figures
20 illustrating the three-dimensional display device according to the present invention.

(First Embodiment of Three-Dimensional Display Device)

25 Fig. 40 is a block diagram illustrating a schematic construction of the first embodiment of a

three-dimensional display device according to the present invention. In Fig. 40, reference numeral 61 denotes a two-dimensional display device; 62, a varifocal lens; 63, a driving device; 64, a synchronization device; 65, a three-dimensional image; 66, an observer; and 67, a two-dimensional image.

In Fig. 40, the two-dimensional display device 61 is well known as a CRT (Cathode Ray Tube), a liquid crystal display, an LED display, plasma display, a projector type display, a vector-scanning type display or the like. The varifocal lens 62 is the optical device as set forth above.

The two-dimensional display device 61 is arranged inside of the focal length of the varifocal lens 62, namely at the position closer to the varifocal lens 62 than the focal length.

The varifocal lens 62 is interposed between the two-dimensional display device 61 and the observer 66, to vary the focal length at a predetermined speed according to an output from the driving device 63, described later.

The driving device 63 is a known signal generator having a predetermined duty ratio and a predetermined period and outputting driving signals

of frequencies f12 and f22 having the same amplitude.

Although this embodiment employs the driving signals of frequencies f12 and 22 having the same
5 amplitude as outputs from the driving device 63, it is may employ signals of frequencies having various amplitudes.

The synchronization device 64 is adapted to synchronize the focal position of the varifocal lens
10 62 and the two-dimensional image displayed on the two-dimensional display device 61. For example, the synchronization device 64 generates a synchronization signal after a lapse of a delay period until the focal length of the varifocal lens
15 62 is varied on the basis from the output from the driving device.

The three-dimensional image 65 is used for explaining the image to be viewed by the observer 66 in the case where the first embodiment of the three-
20 dimensional display device is employed. In this embodiment, the image is displayed as a virtual image.

Eyes of the observer 66 represents a view position of the observer 66. The two-dimensional
25 image 67 represents an image to be displayed on the two-dimensional display device 61, which is

generated by decomposing the three-dimensional image into the two-dimensional image represented on a plane at predetermined intervals according to procedures described later. Namely, the two-dimensional image 67 are a depth sampled image.

Fig. 41 graphically shows a state of variation of the focal length when the varifocal lens is driven by the driving device in the first embodiment. In Fig. 41, the horizontal axis represents a driving time and the vertical axis represents a focal length.

It should be noted that the waveform of the driving signal is rectangular, as shown in Fig. 8B, in which a low frequency f_{21} ($\Delta\epsilon_1 > 0$) and a high frequency f_{22} ($\Delta\epsilon_1 < 0$) are used. The refractive index of the dual-frequency liquid crystal (variable refractive index material) becomes smaller than the refractive index of the transparent material when the dual-frequency liquid crystal is erected perpendicularly to the transparent electrodes 23 and 24. On the other hand, when the dual-frequency liquid crystal is disposed substantially in parallel to the transparent electrodes 23 and 24, the refractive index of the dual-frequency liquid crystal becomes greater than that of the transparent material.

As a result, it is obvious from Fig. 41 that the focal length of the varifocal lens 12 is varied in an analogous sequential manner. The repetition frequency of the low frequency f_{l2} and the high
5 frequency f_{h2} is substantially 30 Hz.

Accordingly, remarkably high speed operation can be achieved, by employing the varifocal lens in the above-described optical device, in comparison with the conventional liquid crystal lens which takes
10 several seconds for resumption.

The operation of the first embodiment of the three-dimensional display device will be discussed with reference to Figs. 42A and 42B.

Fig. 42A is an illustration for explaining
15 operation of the three-dimensional display device, and Fig. 42B is an illustration for explaining the two-dimensional image to be displayed on the two-dimensional display device 61.

In Figs. 42A and 42B, a virtual image 68 is a
20 two-dimensional image formed at a position 69, and a virtual image 110 is a two-dimensional image formed at a position 111. Reference symbol d_{obj} designates a distance between the varifocal lens and the two-dimensional display device; and d_{img} , a distance
25 between the varifocal lens and the imaging point of the virtual image. Fig. 42B shows a three-

dimensional image 112 and an aggregate 113 of the two-dimensional images.

It should be noted that the reason why the minus (-) sign is given to the distance d_{img} between the
5 varifocal lens and the imaging point of the virtual image is that the direction toward the observer 66 from the varifocal lens 62 is taken to be plus (+).

Next, discussion will be given on operation of the first embodiment of the three-dimensional
10 display device in reference to Figs. 40, 42A and 42B. As described above, the position (view position) of the two-dimensional display device is set at a position where the d_{obj} is smaller than the focal length of the varifocal lens 62. Therefore,
15 the two-dimensional image 67 displayed on the two-dimensional display device 61 is observed as a virtual image by the observer 66.

At this time, conforming to the equation (1) below according to a paraxial theory as a theory of
20 optics of the lens, the imaging point 69 of the virtual image 68 of the two-dimensional image 67 can be varied in the depth direction toward the imaging point 111 of the virtual image 110 by varying the focal length of the varifocal lens 62.

25
$$1/d_{obj} + 1/d_{img} = 1/f_o \quad \dots\dots (1)$$

wherein f_0 is a focal length of the varifocal lens 62.

As shown in Fig. 42B, for example, the three-dimensional image 112 is expressed as an aggregate
5 of the two-dimensional images sampled toward the depth direction from the visual direction when the three-dimensional image 112 is picked up or displayed, and the respective two-dimensional images are displayed on the two-dimensional display device
10 61 in a time division manner.

At this time, synchronization of the two-dimensional display device 61 and variation of the focal length of the varifocal lens 62 is established by the synchronization device 64 so that the imaging
15 point of the two-dimensional image to be displayed on the two-dimensional display device 61 accords with the sampling position in the depth direction. Consequently, due to an after image effect of the eyes of the observer 66, the three-dimensional image
20 65 to be displayed on the two-dimensional display device 61 can be observed as an aggregate (virtual image) of the images sampled in the depth direction viewed from the observer 66.

As described above, in the first embodiment of
25 the three-dimensional display device, an image

obtained by sampling the three-dimensional image 112 into two-dimensional images represented on the two-dimensional plane at predetermined intervals is displayed on the two-dimensional display device 61.

5 The two-dimensional images to be displayed on the two-dimensional display 61 are displayed at the same positions as those at the time of sampling based on an output from the synchronization device 64 for generating a signal in synchronism with variation in

10 focal length of the varifocal lens 62. Thus, on the basis of the foregoing equation (1), the imaging point of the two-dimensional image (virtual image) to be displayed on the two-dimensional display device 61 can be varied so that the three-

15 dimensional image 112 can be displayed as the virtual image 65; i.e., an aggregate of the sampled images in the depth direction.

In the first embodiment of the three-dimensional display device, since the observer 66 views the

20 three-dimensional image 65 as the aggregate of the virtual images substantially aligned in the depth direction. Thus, visual cues to depth perception in three-dimensional view such as binocular disparity, convergence, accommodation and movement parallax can

25 be satisfied without causing any discrepancy, and a natural three-dimensional image can be realized.

Moreover, in the first embodiment of the three-dimensional display device, an amount of information necessary for displaying is determined according to the number of samples in the depth direction.

5 Resolution in the visual direction (depth direction) of the human being is known to be lower than resolution in the vertical and horizontal directions. Therefore, the number of the samples in the depth direction can become greatly smaller than
10 that required in the vertical and horizontal directions. According to the present invention, the information amount required for displaying can be remarkably reduced in comparison with the holography.

15 Additionally, since the information amount can be remarkably reduced, the three-dimensional display device in the first embodiment can be applicable to the case of displaying, e.g., a moving picture, which must be displayed at high speed.

20 Furthermore, since the three-dimensional display device in the first embodiment utilizes the normal lens effect by the varifocal lens 62, a coherent light source such as a laser beam source is not required as the light beam source. Furthermore,
25 since an influence of difference of colors in the

two-dimensional image 67 is slight, it is easy to achieve color image display.

Furthermore, since no mechanical driving portion is required, the three-dimensional display device in
5 the first embodiment is advantageous in reduction of a weight and improvement of reliability.

Although in this embodiment two frequencies are used, the number of frequencies should not be limited to two, and the greater number of
10 frequencies may be employed.

(Second Embodiment of Three-Dimensional Display Device)

Fig. 43 is a view showing a schematic
15 construction of a three-dimensional display device in the second embodiment according to the present invention. In the second embodiment shown in Fig. 43, the basic construction is the same as that of the three-dimensional display device in the first
20 embodiment, and different from the first embodiment in that the two-dimensional display device 61 is arranged outside of the focal length as viewed from the varifocal lens 62, and that the three-dimensional image 112, i.e., the aggregate 113 of
25 the two dimensional images is displayed on the two-

dimensional display device 61 in a manner invented in the vertical and horizontal directions

As obvious from Fig. 43, since the two-dimensional display device 61 is arranged outside of the varifocal length as viewed from the varifocal lens 62 in the three-dimensional display device in this second embodiment, the observer 66 may view the three-dimensional image (real image) formed between the varifocal lens 62 and the observer 66.

Fig. 44 is an illustration for explaining operation of the second embodiment of the three-dimensional display device. Hereinafter, description will be given on operation of the second embodiment of the three-dimensional display device with reference to Fig. 44.

In Fig. 44, the real image 116 is a two-dimensional image formed at an imaging point 117, and another real image 114 is a two-dimensional image formed at another imaging point 115.

At first, as shown in Fig. 44, the imaging point 115 of the real image 114 of the two-dimensional image 67 can be varied in the depth direction from the observer 66 toward the imaging point 117 of the real image 116 by varying the focal length of the varifocal lens 62.

Accordingly, similarly to the first embodiment as set forth above, the three-dimensional image is expressed as the aggregate 113 of the two-dimensional images sampled in the depth direction, and the respective two-dimensional images in the aggregate 113 are displayed on the two-dimensional display device 61 in a time division manner. Further, the focal lengths of the two-dimensional display device 61 and varifocal lens 62 are synchronized by the synchronization device 64 so that the imaging points of the respective two-dimensional images accord with the sampling position in the depth direction. Thus, utilizing the after image effect of the human eyes, the three-dimensional image can be reproduced as an aggregate of the sampled images (real image) in the depth direction.

Accordingly, this embodiment of the three-dimensional display device achieves the same advantageous result as that of the first embodiment of the three-dimensional display device. In addition, since the second embodiment of the three-dimensional display device can form the real image, it becomes possible to pick up the two-dimensional image by placing a beaded plate at the imaging point.

Otherwise, by placing a scattering plate at the imaging point, only the two-dimensional image at that position can be viewed.

5 (Third Embodiment of Three-Dimensional Display Device)

Fig. 45 is a block diagram illustrating a schematic construction of a third embodiment of the three-dimensional display device according to the
10 present invention. Reference numeral 151 denotes a projection type display; 152, a shutter; 153, a scattering plate; 154, an image recording and reproducing apparatus; and 155, a synchronization control device.

15 In Fig. 45, the projection type display 151 has been well known. In the third embodiment, a plurality of displays are employed for lowering a depiction speed of the respective projection type displays.

20 The shutters 152 are provided in the respective projection type displays 151, for projecting images from each of projection type displays 151 on the scattering plate 153 in a time division manner.

The scattering plate 153 is of a known type for
25 displaying the image projected from the projection type display 151. For example, the scattering plate

152 is placed within the focal length of the varifocal lens 62, similarly to the first embodiment.

The image recording and reproducing apparatus 154 is of a known type, such as a video recorder. The image recording and reproducing apparatus 154 outputs an image signal to the projection type display 151 connected thereto on the basis of the output from the synchronization control device 155.

10 The synchronization control device 155 controls operation of the image recording and reproducing apparatus so that the image signal can be output in synchronism with variation in the focal length of the varifocal lens 157 on the basis of the output from the driving device 63. Further, the synchronization control device 155 controls the respective shutters 152, for projecting the image of the selected one of the projection type display 151 onto the scattering plate 153.

20 Next, the operation of the third embodiment of the three-dimensional display device according to the present invention will be discussed with reference to Fig. 45. Similarly to the foregoing first embodiment, the three-dimensional image 112 shown in Fig. 42B is expressed as the aggregate 113
25 of the two-dimensional images sampled in the depth

direction. These two-dimensional images are projected in order from the projection type display 151 and displayed in order on the scattering plate 153 in a time division manner by the respective
5 shutters 152. Simultaneously, the image recording and reproducing apparatus 154 and the focal length of the varifocal lens 62 are synchronized such that the imaging point of each two-dimensional image accords with the sampling position. Consequently,
10 the three-dimensional image can be reproduced as an aggregate of the sampled images (virtual images) utilizing the after image effect of the human eyes.

Thus, the same advantageous result can be produced as that of the three-dimensional display
15 devices in the foregoing embodiments. Additionally, a screen size can be increased easily since the projection type display 151, shutter 152 and scattering plate 153, which all have been known.

It should be noted that, in the third embodiment
20 of the three-dimensional display device, it is possible to place the scattering plate 153 and the varifocal lens 157 in a positional relationship similar to the second embodiment in which the scattering plate 153 is placed outside of the focal
25 length of the varifocal lens 157 so as to achieve three-dimensional displaying by projecting

vertically and horizontally inverted images (two-dimensional images) from the image recording and reproducing apparatus 154.

Fig. 46 is view showing another schematic construction of the varifocal lens to be used in the three-dimensional display device. Reference numerals 161 and 162 denotes transparent electrodes; 163, a variable refractive index material; and 164, an aperture.

10 In Fig. 46, the transparent electrodes 161 and 162 has been known and are formed of an ITO film, a ZnOx film or the like. The aperture 164 is formed on the transparent electrode 161, as shown in Fig. 46.

15 The variable refractive index material 163 is formed of a polymer dispersed liquid crystal, a polymer liquid crystal or the like, and its refractive index is varied depending upon a voltage applied to the transparent electrodes 161 and 162.

20 It should be noted that in the varifocal lens in the third embodiment of the three-dimensional display device, the configuration of the aperture 164 formed on the transparent electrode 161 is circular. However, the shape of the aperture is not
25 limited to be circular, and can be variable with respect to the direction of the light beam. For

instance, the aperture may be formed into a strip if the focal length is varied only in one direction.

Although the present invention made by the inventors has been described in detail and particularly in the preferred embodiments, the present invention should not be limited to these embodiments, but can be modified in various ways without departing from the spirit and the scope of the invention.

For example, it is also possible to reproduce a three-dimensional image 172 by employing a line depiction device 171 (such as a laser scanning depiction device or an electron beam scanning depiction device) as a two-dimensional display device to express the three-dimensional image 172 as an aggregate of lines or dots in place of the sampled images in the depth direction, and by varying the focal length of the varifocal lens 62 in accordance with the position of the lines or dot in the depth direction by employing the synchronization device 64, as shown in Fig. 47.

This system is applicable to the foregoing embodiments. This system can produce the same advantageous results as those achieved by the foregoing embodiments. Furthermore, since this system can reduce the number of components required

for achieving the three-dimensional display, thus facilitating analogous (sequential) display in the depth direction.

According to the present invention, the three-dimensional image is displayed by varying the focal length of the varifocal lens 62 so as to vary the imaging point of the image (virtual image or real image) displayed on the two-dimensional display device 171 in the depth direction. Since the resolution in the depth direction of the human being is markedly low at the far position in comparison with that in the near position, it may be possible to reduce the overall information amount by increasing the number of samples at the near position to the observer 66 and reducing the number of samples farther from the observer 66.

As illustrated in Fig. 48, it can be considered that the motion speed of the image by the varifocal lens is not constant in the depth direction.

In this case, if the brightness of the two dimensional images are constant, the image where the motion speed is low appears brighter and the image where the motion speed is high appears darker to make the brightness as viewed by the observer non uniform.

Therefore, it is quite useful to vary the brightness of the two-dimensional image according to the motion speed of the varifocal lens.

As illustrated in Fig. 48, the focal length of the varifocal lens is varied periodically between the position near to the eyes and the position far from the eyes.

In such driving manner driving, there are two cases: (1) from the near position to the far position; and (2) from the far position to the near position. These two motions are reverse in direction, but pass through the same depth positions.

Accordingly, by depicting different images in the cases of (1) and (2), the three-dimensional display device of the present invention can be driven more efficiently.

(Fourth Embodiment of Three-Dimensional Display Device)

With the three-dimensional display devices in the foregoing embodiments, since the two-dimensional images sampled in the depth direction are displayed in time division to be thus integrated into the three-dimensional image by an after image effect, it is impossible to avoid a phantom phenomenon, which

allows the back side or inside of the object which should be hidden from the observer's sight to be viewed transparently. This is an immense obstacle to reproduction of the natural three-dimensional image, and is the reason why the three-dimensional display devices in the foregoing embodiments are used only for reproducing wire frame like images. Hereinafter, a three-dimensional display device capable of avoiding the above-stated drawback will be described with reference to Figs. 49 to 59.

Fig. 49 is a schematic view showing a construction of the fourth embodiment of the three-dimensional display device according to the invention, and Fig. 50 is an illustration for explaining basic operation of the fourth embodiment of the three-dimensional display device for avoiding the phantom phenomenon.

In Figs. 49 and 50, reference numeral 201 denotes a phantom three-dimensional display device; 202, a shutter device; 202A, a shutter element of the shutter device 202; 203, a phantom image (real image); 204, eyes of an observer; 205, a transmitted light beam; 206, a blocked light beam; 207, a portion where blocking, scattering and reflecting functions are affected.

The fourth embodiment uses an example in which a three-dimensional image is reproduced as a real image outside of the phantom three-dimensional display device. The term "Phantom" refers to a phenomenon which allows the back side or inside of an object which should be hidden to be viewed transparently.

As shown in Fig. 49, the fourth embodiment of the three-dimensional display device comprises the phantom three-dimensional display device 201 and the shutter device 202 arranged at a position including the phantom three-dimensional image 203.

The phantom three-dimensional display device 201 is exemplified in a varifocal three-dimensional display device or a depth direction sampling type device such as a varifocal mirror type device, a varifocal lens type device, an oscillation screen type device, a display area layer type device or a rotary type device. The phantom three-dimensional display device 201 reproduces the phantom image 203 by, for example, displaying images sampled in the depth direction in a time division manner. This phantom image is practically displayed with development in the depth direction. Therefore, although it becomes possible to satisfy visual cues to depth perception in the three-dimensional view,

such as binocular disparity, convergence, accommodation and movement parallax without any discrepancy, there arises a problem that the back side or inside to be hidden is viewed transparently.

5 Namely, normally, a light beam is scattered/reflected on the surface of a general three-dimensional object, and simultaneously, a light beam from the back side is blocked. However, the phantom three-dimensional display device can
10 only express the former function. The three-dimensional display device as shown in Fig. 43 is one example of the phantom three-dimensional display device.

The shutter device 202 is a device including a
15 guest-host liquid crystal, a polymer dispersed liquid crystal, a holographic polymer dispersed liquid crystal or the like; or a device including a photo reactive element in which the state of an imaging point is turned into a light blocking state,
20 a light scattering state or a light reflecting state by converged light at the imaging point of a real image.

Next, the basic operation of the fourth embodiment of the three-dimensional display device
25 for avoiding the phantom phenomenon will be discussed with reference to Fig. 50.

As shown in Fig. 50, the fourth embodiment of the three-dimensional display device is constructed by arranging the shutter elements 202A forming the shutter device 202. for example, in the vicinity of the sampling positions in the depth direction (for simplicity of illustration, only one is shown in the drawing). At the position corresponding to the image sampled in the depth direction in the vicinity of the shutter element during a period when the phantom three-dimensional image 203 behind of the shutter element 202A (as viewed from the eyes 204 of the observer) is reproduced, the function to block, scatter or reflect the light beam is made effective for maintaining a transparent condition at other positions for other periods. Thus, the light beam coming from behind of the shutter element (as viewed from the eyes 204 of the observer) can be blocked or attenuated. This means that the frontal portion of the object blocks the light beam from the back portion, and the condition where the backside of the object cannot be seen can be simulated.

Accordingly, the phantom portion of the phantom three-dimensional image 203 can be made invisible by arranging the shutter elements 202A in the vicinity of the necessary sampling position in the depth direction. Therefore, it is possible to obtain a

natural three-dimensional reproduced image without any phantom image.

Since the images sampled in the depth direction to be supplied to the phantom three-dimensional display device 201 can be also used as information to the shutter device 202, an information amount required for displaying the three-dimensional image excluding the phantom image is equal to that required for phantom three-dimensional display device 201, thus preventing any increase in information amount.

Furthermore, the information amount is mainly determined by the number of images sampled in the depth direction. Here, it has been known that the resolution of the human being in the depth direction is lower than that in the vertical and horizontal direction. Therefore, the number of images sampled in the depth direction can be remarkably reduced in comparison with that in the vertical and horizontal direction.

Accordingly, the fourth embodiment is advantageous in that the required information amount can be markedly reduced in comparison with that required for holography and so forth. Therefore, the three-dimensional display device in the fourth embodiment can be satisfactorily applied to the case

where, for example, a moving picture must be displayed at a high speed.

Moreover, since the fourth embodiment requires only addition of the shutter device 202, an
5 influence by a color difference of the displayed image can be reduced to facilitate displaying in color. Further, since the fourth embodiment does not include mechanical driving portions, it is suitable for reduction of a weight and improvement
10 of reliability.

Although the fourth embodiment uses an example in which most of the light beam from the backside is blocked by the shutter device 202, a light blocking ratio of the shutter device 202 can be set to a
15 desired value so as to easily express a semi-transparent or transparent three-dimensional object (such as glass or transparent plastic).

(Fifth Embodiment of Three-Dimensional Display
20 Device)

The fourth embodiment as set forth above uses one example according to the present invention, in which the three-dimensional image is a real image. It is also possible to avoid the phantom phenomenon
25 even if the three-dimensional image is a virtual image. In the fifth embodiment, a description will

be given on a varifocal lens type device as a phantom three-dimensional display device in which a phantom three-dimensional image is reproduced as a virtual image. The fifth embodiment of the three-
5 dimensional display device will be discussed hereinafter with reference to Figs. 51 and 52.

Fig. 51 is a view showing a schematic construction of the fifth embodiment of the three-dimensional display device according to the present
10 invention, and Fig. 52 is an illustration for explaining basic operation of the fifth embodiment of the three-dimensional display device for avoiding a phantom phenomenon.

In Figs. 51 and 52, reference numeral 202
15 denotes a shutter device; 202A, a shutter element of the shutter device 202; 204, the eyes of an observer; 205, a transmitted light beam; 206, the blocked light beam; 207, a portion where blocking, scattering and reflecting functions are effected;
20 208, a two dimensional display device; 209, the varifocal lens; 210, a phantom three-dimensional image (virtual image); and 211, a virtual image of the shutter element 202A.

As shown in Fig. 51, the fifth embodiment of the
25 three-dimensional display device comprises the two-dimensional display device 208, a varifocal lens

type phantom three-dimensional display device constructed of the varifocal lens 209, and the shutter device 202 interposed between the varifocal lens 209 and the two-dimensional display device 208.

5 The two-dimensional display device 208 is, for example, a CRT, a liquid crystal display, an LED display, a plasma display, a projection type display, a line depiction type display and the like. For example, a laser scan depiction device, a CRT
10 (electron beam scan depiction device) and the like can be employed.

 The varifocal lens 209 comprises a fixed focus lens, a variable refractive index material, and electrodes sandwiching the lens and the material
15 there between.

 Here, the two dimensional display device 208 is arranged within the focal length of the varifocal lens 209. Therefore, the image to be viewed becomes a virtual image.

20 The phantom three dimensional display device reproduces the virtual image by displaying the sampled images in the depth direction in a time division manner, for example. The phantom three-dimensional display device uses an example shown in
25 fig. 40.

Next, the basic operation for avoiding the phantom phenomenon in the fifth embodiment of the three-dimensional display device will be discussed with reference to Fig. 52.

5 Unlike the fourth embodiment, in the fifth embodiment, it is meaningless to place the shutter device 202 at the virtual image position since the functions of blocking, scattering and reflecting of the light beam cannot be effected. The light beams
10 are actually converged at the real imaging point. In contrast, the light beams look like coming from the virtual image, and are not converged actually.

 Therefore, the shutter elements 202A (only one is shown for simplification of illustration) of the
15 shutter device 202 is placed at a position between the two-dimensional display device 208 and the varifocal lens 209, which position is optically equivalent to the virtual image position and the light beam actually passes. By this arrangement,
20 the shutter device 202 is also projected at the virtual image position by the effect of the varifocal lens 209. Thus, it is possible to produce the same advantageous result as that of the fourth embodiment.

25 Namely, at the position corresponding to the sample images in the depth direction during a period

when the phantom three-dimensional image 210 behind
of the virtual image (211) of the shutter elements
202A (as viewed from the observer 204) is
reproduced, the function for blocking, scattering or
5 reflecting the light beam is made effective, and a
transparent condition is maintained at other timings
and other positions. Thus, the light beam coming
from behind of the shutter element 202A (as viewed
from the observer 204) is blocked or attenuated for
10 the observer. This means that the front portion of
the object blocks the light beam from the rear
portion, and the condition where the backside of the
object is invisible, can be simulated.

Accordingly, by this embodiment, similarly to
15 the fourth embodiment even the pseudo of phantom
three-dimensional image 210, the phantom portion can
be made invisible. Thus, it is possible to obtain a
natural three-dimensional reproduced image excluding
any phantom image.

20

(Sixth Embodiment of Three-Dimensional Display
Device)

In the foregoing fifth embodiment, the shutter
device is arranged at a position which is optically
25 equivalent to the phantom three-dimensional image of
the virtual image and in which the light beam

actually passes. The advantageous result of the present invention can be achieved by arranging the shutter device at a position which is optically equivalent to the phantom three-dimensional image of the image and in which the light beam actually passes, irrespective of a real image or a virtual image of the phantom three-dimensional image.

The sixth embodiment uses an example in which a varifocal lens type device is employed as the phantom three-dimensional display device and the phantom three-dimensional image is reproduced as a real image. Discussion will be given on the sixth embodiment of the three-dimensional display device with reference to Figs. 53 and 54.

Fig. 53 is a view showing a schematic construction of the sixth embodiment of the three-dimensional display device, and Fig. 54 is an illustration for explaining the basic operation for avoiding a phantom phenomenon in the sixth embodiment of the three-dimensional display device.

In Figs. 53 and 54, reference numeral 202 denotes a shutter device; 202A, a shutter element of the shutter device 202; 203, a phantom three-dimensional image (real image); 204, an observer; 205, a transmitted light beam; 206, a blocked light beam; 207, a portion where blocking, scattering and

reflecting functions are effected; 208, a two-dimensional display device; and 209, a varifocal lens.

Like the fifth embodiment, the sixth embodiment
5 of the three-dimensional display device comprises the varifocal lens type phantom three-dimensional display device including the two-dimensional display device 208 and the varifocal lens 209, and the
shutter device 202 interposed between the two-
10 dimensional display device 208 and the varifocal lens 209, as shown in Fig. 53. Here, the two-dimensional display device 208 and the varifocal lens 209 are arranged outside of the focal length of the varifocal lens 209 so that an image to be viewed
15 becomes a real image, i.e., a phantom three-dimensional image 203.

Although like the fifth embodiment, the shutter device 202 may be arranged at a position of the phantom three-dimensional image 203, it can be
20 arranged at a position which is optically equivalent to the phantom three-dimensional image of the virtual image and in which the light beam actually passes, as shown in Figs. 53 and 54 (only one is shown for simplification of illustration). With
25 this arrangement, the shutter device 202 is also projected on the real image position by the effect

of the varifocal lens 209. Thus, it is possible to produce the same advantageous result as that of the fourth embodiment.

Namely, at the position corresponding to the
5 sample images in the depth direction, during a period when the phantom three-dimensional image 203 behind

of the position of the real image of the shutter
elements 202A (as viewed from the observer 204) is
10 reproduced, the function for blocking, scattering or reflecting the light beam is made effective, and a transparent condition is maintained at other timings and other positions. Thus, the light beam coming from behind of the shutter element 202A (as viewed
15 from the observer 204) is blocked or attenuated for the observer. This means that the front portion of the object blocks the light beam from the rear portion, and the condition where the backside of the object is invisible can be simulated.

20 Thus, in the sixth embodiment, the advantageous result of the present invention can be achieved by arranging the shutter device at the position which is optically equivalent to the phantom three-dimensional image of the virtual image and in which
25 the light beam actually passes, and the natural

three-dimensional image without any phantom image can be obtained.

For example, by the use of the depth sample type phantom three-dimensional display device, when a
5 part of the display device moves to the phantom image position, it is physically difficult to arrange the shutter device 202 at that position. Therefore, it may be possible to optically shift the position of the phantom three dimensional image by
10 employing an optical system such as a lens or a mirror, and to arrange the shutter device 202 at the shifted position, as shown in Fig. 55, for example. Even in this case, it is obvious from the sixth embodiment that the advantageous result of the
15 present invention can be sufficiently achieved.

In this embodiment, like the three-dimensional image 203 shown in Fig. 53, a region where the three-dimensional image 203 is reproduced can be set in a space where no object such as the device
20 exists, thereby offering an advantage of reducing a frame canceling and the like. Here, the frame canceling means a phenomenon that if an object exists within the region where the three-dimensional image is reproduced, the configuration and the like
25 of the object may influence on the recognition process of a three-dimensional image by the human

being such that the position of the three-dimensional image is shifted by the influence of presence of the object, or the three-dimensional image sticks on the object to be viewed as the two-dimensional image; or the observer feels a strange feeling that the three-dimensional image moves in the opposite direction, when he moves his head. Further, in this embodiment, since the region where the three-dimensional image 203 is reproduced is a mere space, it is possible to advantageously arrange an object over, under or beside the three-dimensional image so as to reduce the frame canceling.

15 (Embodiment of Shutter Device to be Employed in Fourth to Sixth Embodiments)

An embodiment of the shutter device to be employed in the present invention will be illustrated in Figs. 56A to 58.

20 One example of the guest host liquid crystal element to be employed in the shutter device is shown in Figs. 56A. and 56B. In Fig. 56A, reference numeral 321 denotes a guest-host liquid crystal layer; 321A, a liquid crystal; 321B, a dichroic dye; 25 322 and 323, alignment layers; 324 and 325,

electrodes; 326, a power source (applied voltage);
and 327, a power switch.

As shown in Fig. 56A, the guest-host liquid
crystal element comprises the guest-host liquid
5 crystal layer 321 composed of a mixture of the
dichroic dye (e.g., anthraquinone type dichroic dye
or azo type dichroic dye), the liquid crystal (e.g.,
nematic liquid crystal), the alignment layers 322
and 323 and the electrodes 324 and 325 sandwiching
10 the guest-host liquid crystal.

When no voltage is applied between the
electrodes 324 and 325, the liquid crystal 321A is
aligned in parallel to the alignment layers 322 and
323 by anchoring force of the alignment layer 322
15 and 323. Accordingly, the dichroic dye 321B is also
aligned in parallel to the alignment layers, to
become, e.g., black and absorb the light beam.
Therefore, the light beam coming from the backside
is absorbed by the dye so that the intensity of the
20 light beam to be transmitted forward can be reduced
remarkably.

As shown in Fig. 56B, when a voltage higher than
or equal to a threshold voltage of the liquid
crystal 321A is applied between the electrodes 324
25 and 325, the liquid crystal 321A is aligned
perpendicularly to the alignment layers due to its

own dielectric constant anisotropy. Accordingly, the dichroic dye 321B is also aligned perpendicularly to the alignment layers, to thus become transparent, for example. Thus, in this
5 guest-host liquid crystal element, transmitting and blocking of the light beam can be switched by the voltage, and therefore, the shutter function required in the present invention can be realized.

Since the present invention required only to
10 transmit and block the light beam by the voltage, a similar effect can be produced by a polymer dispersed guest-host liquid crystal element, in which the guest-host liquid crystal is dropwise dispersed in the polymer.

15 Fig. 57 shows one embodiment of the polymer dispersed liquid crystal element to be employed in the shutter device. The polymer dispersed liquid crystal element comprises a polymer dispersed liquid crystal layer 328, in which the liquid crystal
20 (e.g., nematic liquid crystal) droplets 328B are dispersed in a transparent polymer (e.g., acryl type polymer) 328A, and electrodes 324 and 325 sandwiching the layer 328.

When no voltage is applied between the
25 electrodes 324 and 325, the liquid crystal droplets 328A are oriented randomly by the anchoring force of

alignment of the polymer around the droplets 328B so that the light beam is scattered by birefringence of the droplets 328B. Therefore, the light beam coming from the backside is scattered by the polymer

5 dispersed liquid crystal, and then, its intensity is reduced. Next, when a sufficient voltage is applied between the electrodes 324 and 325, the liquid crystal is aligned perpendicularly to the electrodes 324 and 325 due to its own dielectric constant
10 anisotropy so that its refractive index becomes substantially equal to that of the polymer 328A thus to become transparent. Thus, in this polymer dispersed liquid crystal element, transmitting and scattering of the light beam can be switched by the
15 voltage. Therefore, the shutter function required in the present invention can be realized.

Since the present invention requires only to control transmitting and scattering of the light beam by the voltage, the similar effect may be
20 produced by employing a polymer dispersed liquid crystal, in which the polymer is dispersed within the liquid crystal in a network fashion.

Fig. 58 shows one embodiment of a holographic polymer dispersed liquid crystal element to be
25 employed in the shutter device. The holographic polymer dispersed liquid crystal element comprises a

holographic polymer dispersed liquid crystal layer 329, in which the liquid crystal (e.g., nematic liquid crystal) droplets 328B are dispersed in a laminated manner in the transparent polymer (e.g., acryl type polymer) 328A, as shown in Fig. 58, and the electrodes 324 and 325 sandwiching the layer 329.

When no voltage is applied between the electrodes 324 and 325, the liquid crystal droplets 328A are oriented randomly by the anchoring force of alignment of the polymer around the droplets 328B so that the light beam is scattered by birefringence of the liquid crystal droplets 328B, and reflected by Bragg reflection of multi layer structure of the polymer layer 328A and the layer of the liquid crystal droplets 328B. Therefore, the light beam coming from the backside is refracted to, e.g., the back side by the holographic polymer dispersed liquid crystal element 329, and the intensity of the light beam transmitted forward is markedly reduced.

Next, when a sufficient voltage is applied between the electrodes 324 and 325, the liquid crystal is aligned perpendicularly to the electrodes 324 and 325 due to its own dielectric constant anisotropy so that its refractive index becomes

substantially equal to that of the polymer 328A to thus become transparent.

Thus, in this polymer dispersed liquid crystal element, transmission and reflection of the light beam can be switched by the voltage. Therefore, the shutter function required in the present invention can be realized. Here, it is important for the present invention to attenuate the light beam intensity to the observer at the front side.

10 Therefore, in this element, it is not essential to cause mirror surface reflection, but reflection containing scattering factor or deflection to a region where the observer is not present may be sufficiently satisfactory. It is also clear that

15 the light intensity to the observer can be reduced owing to a change in Bragg reflection angle by varying an angle of the multi-layer structure of the layer 328A polymer and the liquid crystal droplets layer 328B in the holographic high polymer dispersed

20 liquid crystal element 329.

It is also clearly effective to employ the guest-host liquid crystal shown in Fig. 56A as the liquid crystal portion of the high polymer dispersed liquid crystal and the holographic polymer dispersed

25 liquid crystal respectively shown in Figs. 57 and 58.

(Seventh Embodiment of Three-Dimensional Display Device)

The seventh embodiment of the three-dimensional display device is substantially constructed similarly to the foregoing fourth embodiment shown in Fig. 49, and comprises the phantom three-dimensional display device for reproducing the real image of the phantom three-dimensional image 203 and the shutter device 202 arranged at the positions including the phantom three-dimensional image 203. Here, the shutter device 202 includes a light beam reactive element (e.g., a photochromic material, a material causing a photostructural change and a material containing a liquid crystal, or an element containing a liquid crystal in which nematic-isotropic phase transition temperature is varied by a photostructural change), in which a converged light beam at an imaging point of a real image brings the imaging point into a beam shuttering, scattering or reflecting state.

Fig. 59 is an illustration showing the basic operation of the seventh embodiment of the three dimensional display device. As shown in Fig. 59, a phantom three-dimensional display device 201 reproduces the phantom three-dimensional image 203 of the real image by displaying depth sample images

in a time division manner. The shutter elements 202A forming the shutter device 202 are arranged at the positions including the phantom three-dimensional image 203. When the three-dimensional image is reproduced from the front side as viewed from the observer, once the phantom image is reproduced (left of Fig. 59), at the imaging point of the real image in the shutter device 202, the point is brought into a light beam blocking, light beam scattering or light beam reflecting state by the action of the light beam reactive element (right in Fig. 59). By this, for a predetermined period when the phantom three-dimensional image 203 of the backside (as viewed from the observer) portion is reproduced, the light beam coming from the phantom three-dimensional image of the backside (as viewed from the eyes 204 of the observer) is blocked or attenuated. This is equivalent to the fact that the front portion of the object blocks the light beam from the rear portion. Further, the condition where the backside of the object is invisible can be successfully simulated.

Accordingly, the seventh embodiment of the three-dimensional display device can make the phantom portion invisible so as to obtain the

natural three-dimensional image without any phantom image.

In the seventh embodiment of the three-dimensional display device, it is not required to
5 input particular information into the shutter device, thus preventing an increase in required information amount. Furthermore, it becomes unnecessary to drive the liquid crystal by the voltage.

10 Discussion will be given on one embodiment of the light beam reactive element. At first, there is a photochromic material which is brought into a light beam blocking state by irradiation of light beam. This utilizes a phenomenon to cause isolation
15 of, for example, silver fine particles by irradiation of light beam and return to become a transparent compound when the light beam is blocked.

It is possible to switch transmission/scattering and transmission/reflection of light beam by
20 dropwise dispersing in the polymer a mixture of a material such as azobenzene type polymer causing a photostructural change such as a cis-trans structure variation by irradiation of light beam and the liquid crystal. Namely, the shape of the material
25 is varied due to the photostructural change, to vary the alignment condition of the liquid crystal and

vary a difference in refractive index between the liquid crystal and the polymer for switching transmission and scattering. Furthermore, it is also clear that reflection and transmission by Bragg reflection can be switched by forming the liquid crystal mixture layer and the polymer layer in a laminated manner.

It is also effective to dropwise disperse, in the polymer, a material containing a liquid crystal, nematic-isotropic phase transition temperature of which is varied due to structural variation or temperature variation by irradiation of light beam. In the nematic phase, the light beam is scattered due to birefringence of the material. On the other hand, in the isotropic phase, birefringence is eliminated so that the light beam becomes transparent. Furthermore, it is also clear that reflection and transmission by Bragg reflection can be switched by forming the liquid crystal mixture layer and the polymer layer in a laminated manner.

Although the present invention has been illustrated and described with respect to the preferred embodiments thereof, it should be understood by those skilled in the art that the present invention is not limited to the specific embodiments set out above, and that various

modifications and alternations can be added thereto without departing from the spirit and scope of the present invention.

5 (First Embodiment of Head-Mount Display Device)

Fig. 60 is a perspective view showing a schematic construction of a first embodiment of a head-mount display device according to the present invention, and Fig. 61 is a plan view of the device
10 of Fig. 60, on a plane including eyes of an observer.

In Figs. 60 and 61, reference numerals 411R and 411L denote two-dimensional display devices such as a CRT device, a liquid crystal display device, an EL
15 display device, a plasma display device, a laser scanning type depiction device and a projection type display device. Reference numerals 412R and 412L denote varifocal lenses such as liquid crystal lens. Reference numerals 413R and 413L are control devices
20 which controls the two-dimensional display devices 411R and 411L and the varifocal lenses 412R and 412L. Reference numerals 414R is a right eye head-mount display device which comprises the two dimensional-display device 411R, the varifocal lens
25 412R and the control device 413R. Reference numeral 414L is a left eye head-mount display device which

comprises the two-dimensional display device 411L,
the varifocal lens 412L and the control device 413L.
Reference numeral 415R denotes right eye; 415L, a
left eye; 416R and 416L, display images; 417, a
5 virtual image; and S, a partition.

The varifocal lens in the head-mount display
device is the optical device set forth above in
detail.

As shown in Figs. 60 and 61, the first
10 embodiment of the head-mount display device
comprises the right eye head-mount display device
414R including the two-dimensional display device
411R, the varifocal lens 412R and the control device
413R; and the left eye head-mount display device
15 414L including the two-dimensional display device
411L, the varifocal lens 412L and the control device
413L, similarly to the right eye head-mount display
device 414R. The right eye head-mount display
device 414R is worn on the right eye 415R and the
20 left eye head-mount display device 414L is worn on
the left eye 415L, respectively.

With the construction set forth above, when a
display image 416R of the two-dimensional display
device 411R is viewed by the right eye 415R through
25 the varifocal lens 412R and a display image 416L of
the two-dimensional display device 411L is viewed by

the left eye 415L through the varifocal lens 412R, a virtual image 417 is formed. If the focal lengths of the varifocal lenses 412R and 412L are varied, the depth position of the virtual image is varied as shown in Fig. 62, to thus form another virtual image 418. As shown in Fig. 63, a three-dimensional image can be expressed as an aggregate of two-dimensional images sampled in the depth direction (hereinafter referred to as "depth sampled image").

10 The depth sampled images are displayed in sequence on the two-dimensional display devices 416R and 416L, and then, the control devices 413R and 413L varies the focal lengths of the varifocal lenses 412R and 412L in conformity to the displayed
15 images. Thus, the three-dimensional image can be expressed as an aggregate of the sampled images to realize a varifocal type three-dimensional display device.

 In the first embodiment set forth above, the
20 virtual image is varied in the depth direction, in practice. Therefore, discrepancy between accommodation and the binocular disparity or convergence, which has been caused in the conventional method, can be avoided. Accordingly,
25 it is possible to satisfy accommodation, binocular disparity, convergence as visual cues to depth

perception in three-dimensional view, to thus realize a natural three-dimensional view.

In the first embodiment, as the focal lengths (including positive and negative) of the varifocal
5 lenses 412R and 412L are made smaller, the position of the virtual image in the depth direction is more distant from the eyes, and the images displaced on the two-dimensional display devices 416R and 416L are enlarged accordingly. In order to make the size
10 of the virtual image constant, the size of the displayed image of the two-dimensional display devices 416R and 416L has to be varied corresponding to motion of the focal lengths of the varifocal lenses 412R and 412L.

15 Since, with this nature, the visual field covered by the two-dimensional display device becomes greater as the length from the eyes becomes longer, it becomes possible to realize a natural condition similar to the visual field of the human
20 being.

Furthermore, since the number of, for example, pixels or display lines of the two-dimensional display devices 416R and 416L are not varied, a size of the pixel or a width of the display line becomes
25 greater as a distance of the virtual image from the eyes becomes longer. However, since the visual

angle from the eye is not changed, definition of the image which the human being feels, will be held unchanged.

Fig. 64 is a graph illustrating a relationship between visual cues of depth perception and depth perceptivity, and shows depth perceptivity approximated from measured and calculated values with respect to respective three-dimensional sense factors.

Fig. 65 is a graph illustrating the correspondence and allowable range of convergence and accommodation. A central solid line at 45° represents that the convergence and accommodation are completely corresponded. The region in the vicinity of the 45° solid line is a range allowable at certain focal depth. Although the range is slightly different since visual acuity (ϵ) and blur detection ability (δ) are employed as allowable levels, it is quite narrower than a binocular fusional area of stereoscopy. The outer curve shows a sort of binocular fusion limits; the solid line with black dots represents maximum binocular fusion image limit (allowable convergence limit); the dotted line shows a range in which a fusion image condition is established from twin image condition (fusion limit); and the broken line represents

binocular fusion limit at an image display time of 0.5 sec. (convergence limit of display at a short period of 0.5 sec.): With respect to the moving picture, long-period observation may cause

- 5 considerable fatigue by the three-dimensional effect out of the range indicated by the broken line.

Reference symbol MW represents α convergence angle; and D, a diopter.

- According to the present invention, when the
10 depth sampling is employed, it becomes necessary to define the number of sampling. Here, the accommodation of human eyes is effective only when the visual range is short (less than or equal to 2m), as shown in Fig. 64. Moreover, resolution in
15 the depth direction is relatively as low as 1/10 or more of the visual range. There is also an allowable range of the convergence angle, as illustrated in Fig. 65. Therefore, in practice, a natural three-dimensional image can be realized if
20 the number of the depth sampling ranges from 20 to 40.

- Although, in the first embodiment, the three-dimensional image is realized as an aggregate of the depth sampled images. It is clear that the three-
25 dimensional image can be realized in various other ways, e.g., an aggregate of lines.

It should be noted that the construction shown in Figs. 60 and 61 is one example which makes the device compact by bending the optical path employing a mirror, lens, prism or the like.

5

(Second Embodiment of Head-Mount Display Device)

Fig. 66 shows a schematic construction of a second embodiment of the head-mount display device according to the present invention. In Fig. 66,
10 reference numerals 421R and 421L denote two-dimensional display devices; 422R and 422L, varifocal lenses, 423R and 423L, control devices; 424R and 424L, deflection devices; 425R and 425L, display images; and 417, a virtual image. Examples
15 of the deflection devices 424R and 424L are a liquid crystal prism, a movable mirror, a liquid prism and the like. The second embodiment is adapted to easily establish the natural correspondence between the convergence angle and accommodation.

20 The second embodiment of the head-mount display device comprises the two-dimensional display devices 421R and 421L, the varifocal lenses 422R and 422L and the control devices 423R and 423L for controlling the devices 421R and 421L and the lenses
25 422R and 422L, as shown in Fig. 66.

In the head-mount display device, in order to generate a large convergence angle as the depth position of a three-dimensional image approaches eyes, it is necessary to make the right and left images observed by the right and left eyes closer to the midpoint between both the eyes. Since, in the first embodiment of the head-mount display device, this operation is performed by using the two-dimensional display devices 421R and 421L, the display images are displayed closer toward the midpoint between the right and left eyes. Therefore, control of the display images of the two-dimensional display devices 421R and 421L becomes quite complicated. Additionally, if the convergence angle is varied significantly, it becomes necessary to make the two-dimensional display device greater in the lateral direction beyond the visual field.

To the contrary, in the second embodiment, the right and left images in the lateral direction for forming the convergence angle are moved by the deflection devices 424R and 424L. Namely, the operations of the two-dimensional display devices 421R and 421L and the varifocal lens 422R and 422L are similar to those of the first embodiment. However, as the focal lengths of the varifocal lenses 422R and 422L become longer and the virtual

images of the display images 425R and 425L of the two-dimensional display devices 421R and 421L approach closer to the right and left eyes in the depth direction. the display images of the two
5 dimensional display devices 421R and 421L approach toward the center position midpoint between the right and left eyes by the deflection devices 424R and 424L.

Consequently, in the second embodiment of the
10 head-mount display device, the two-dimensional display and the convergence angle control can be independently controlled with ease. Further, the entire screen surfaces of the two-dimensional display devices 421R and 421L can be effectively
15 used. Namely, the convergence angle becomes small when the virtual image 417 is farther from the right and left eyes, while the convergence angle becomes greater when the virtual image 417 is closer to the right and left eyes. Thus, the convergence angle
20 and accommodation can be easily satisfied.

Although in the second embodiment, the deflection devices 424R and 424L are located closer to the two-dimensional display devices 421R and 421L than the varifocal lens 422R and 422L. However, it
25 is clear that the same advantageous result can be achieved even in the case where the deflection

devices 424R and 424L are located closer to the right and left eyes than the varifocal lenses 422R and 422L.

Moreover, although in the second embodiment as shown as Fig. 66, the deflection devices 424R and 424L and the varifocal lenses are provided separately, the same advantageous result can be achieved even in the case of variable optical devices 426R and 426L in which the deflection devices 424R and 424L and the varifocal lenses are integrated, as shown in Fig. 67. Thus, such construction is quite effective in making the device compact.

15

INDUSTRIAL APPLICABILITY

As set forth above, the optical device according to the present invention enables high speed operation by varying the frequency of the voltage to be applied to the variable refractive index material so as to vary its refractive index and by varying the optical property of the device formed together with the transparent material having the desired curved surface configuration. Furthermore, since the force of exerted by the electric field can be used constantly, the operating speed can be made

higher by increasing the strength of the electric field.

In the optical device according to the present invention, the force exerted by the electric field
5 can vary the refractive index of the variable refractive index material. Moreover, since the transparent electrodes are not provided on the transparent material layer on the side of the variable refractive index material, the influence of
10 the surface configuration of the transparent material layer becomes small, to easily achieve uniformity of the variation in optical property.

Since the transparent electrodes are not provided on the transparent material layer on the
15 side of the variable refractive index material in the optical device according to the present invention, it becomes unnecessary to form a film on a portion having a complex configuration, to thus facilitate fabrication. Furthermore, since the
20 transparent electrodes are not provided on the transparent material layer on the side of the variable refractive index material, the distance between the electrodes can be maintained substantially equal. Additionally, since the
25 transparent material layer is constantly present between the transparent electrodes, degradation in

insulating, property or short-circuiting can be successfully avoided.

Further, in the optical device according to the present invention, the refractive index of the
5 variable refractive index material is periodically varied according to the frequency of each voltage to select the intermediate value, thereby achieving sequential variation of the optical property.

The optical device according to the present
10 invention can maintain the desired refractive index by utilizing the state maintaining characteristics of the variable refractive index material while the voltage supply is stopped. Therefore, it becomes possible to vary the refractive index at a high
15 speed but in a non-periodic manner.

The optical device according to the present invention sequentially varies the refractive index according to a voltage ratio of the voltages having different frequencies in superimposing manner and to
20 be applied to the variable refractive index material, so as to vary the optical property of the device sequentially, enabling high-speed driving with sequential variation, unlike the conventional device which cannot be driven at a high speed.
25 Furthermore, since the force exerted by the electric field can be constantly used, the further speeding-

up can be achieved by increasing the strength of the electric field.

The optical device according to the present invention can maintain the desired refractive index by utilizing the state maintaining characteristics of the variable refractive index material while the voltage supply is stopped. Therefore, it becomes possible to vary the refractive index at a high speed but in a non-periodic manner.

10 The optical device according to the present invention can achieve a uniform alignment condition in a wide domain region under the driving condition where the liquid crystal is aligned in parallel to the alignment layer. Thus, variation of the refractive index of the liquid crystal can be efficiently transferred to the incident light beam. In addition, scattering of the light beam caused by the random orientation of the liquid crystal and the resultant cloudiness can be successfully avoided.

20 Furthermore, the optical device according to the present invention is constructed in such a manner as to reflect the light beam, efficiently transferring the variation of the refractive index of the variable refractive index material to the incident light beam. Further, various functions can be realized irrespective of the polarizing condition of

the incident light beam. Therefore, various optical devices, such as an active mirror and a half mirror, capable of varying the optical property can be realized.

5 In addition, the optical device according to the present invention has the driving device which can constantly supply the voltage having the amplitude greater than or equal to the voltage amplitude, at which the liquid crystal is effectively and
10 statistically aligned in the frequency of the voltage, to thus generate an electrically hydrodynamic motion in the molecules of the liquid crystal. Consequently, the direction of the molecules of the liquid crystal is oscillated
15 between the state where the molecules of the liquid crystal are aligned perpendicularly or in parallel to the electrode and the state where the molecules of the liquid crystal are slightly inclined in synchronism with a frequency twice as high as that
20 of the applied voltage. Therefore, the optical device according to the present invention can vary the optical property at a high speed, sequentially, periodically and uniformly. Furthermore, since it becomes unnecessary to form the film into
25 complicated surface configuration, production can be facilitated.

The three-dimensional display device according to the present invention drives the imaging point shifting portion on the bases of the driving signal generated by the driving portion, and the

5 synchronizing portion updates the two-dimensional images to be displayed on the display portion sequentially in a predetermined order on the basis of the output from the driving portion. Therefore, position of the two-dimensional image to be the

10 displayed on the display portion can be varied in the direction of the eyes of the observer so that the observer may three-dimensionally view the two-dimensional images on the two-dimensional plane displayed on the display means.

15 The three-dimensional display device according to the present invention can satisfy the visual cues to depth perception in three-dimensional view such as binocular disparity, convergence, accommodation and movement parallax without using any eyeglasses

20 and display the moving picture which can be re-written electrically.

Otherwise, the phantom three-dimensional display device according to the present invention is additionally provided with the shutter device which

25 can switch in timewise and/or spacewise among the light beam transmitting state, light beam scattering

state and light beam reflecting state. In the phantom three-dimensional display device, the shutter device is disposed at the position including the position where the phantom three-dimensional image is reproduced. This three-dimensional display device activates the function for blocking or scattering the light beam of the shutter elements of the shutter device when the phantom three-dimensional image at the backside as viewed from the observer is reproduced. As a result, many of the visual cues to depth perception in three-dimensional view can be satisfied and the natural three-dimensional image without any phantom phenomenon can be electrically reproduced in the form of the moving picture.

The head-mount display device according to the present invention, comprising the two-dimensional devices and the varifocal lenses are worn on the right and left eyes of the human being so that the display images of the two-dimensional display devices are observed through the varifocal lenses, and the focal lengths of the varifocal lens are varied for varying the position of the virtual image of the display image of the two-dimensional display device in the depth direction. As a result, it is possible to reproduce the three-dimensional image

without any discrepancy in visual cues to depth
perception in three-dimensional view such as
binocular disparity, convergence and accommodation
at a high speed in an electrically rewritable
5 manner.

WHAT IS CLAIMED IS:

1. An optical device comprising:
 - a transparent material layer having a desired
 - 5 curved surface configuration;
 - a layer including a variable refractive index material having a dielectric constant anisotropy and having a property in which a sign of a difference $\Delta\epsilon$ in dielectric constant due to the anisotropy is
 - 10 reversed at driving frequencies f_1 and f_2 ;
 - at least two transparent electrodes arranged to sandwich said transparent material layer and said layer including said variable refractive index material; and
 - 15 a driving device supplying a voltage including said driving frequencies f_1 and f_2 between said transparent electrodes.
2. An optical device as set forth in claim 1,
- 20 wherein said driving device sequentially applies voltages V_1 to V_N having primary frequencies f_1 to f_N ($N \geq 2$) to said transparent electrodes for a predetermined period of time and at a predetermined interval.

25

3. An optical device as set forth in claim 2,
wherein when sequentially applying voltages V_1 to V_N
having primary frequencies f_1 to f_N ($N \geq 2$) to said
transparent electrodes for a predetermined period of
5 time and at a predetermined interval, said driving
device temporarily suspends the supply of the
voltage at a desired phase of said interval and
subsequently resume the supply of the voltage.
- 10 4. An optical device as set forth in claim 1,
wherein a dual-frequency liquid crystal is employed
as said variable refractive index material having
the refractive index anisotropy and the dielectric
constant anisotropy and having a difference $\Delta\epsilon$ of the
15 different dielectric constant which is reversed at
the driving frequencies f_1 and f_2 .
- ✓ 5. An optical device as set forth in claim 4,
wherein a material having a low wettability with the
20 liquid crystal is arranged at least one of positions
contacting said layer of the liquid crystal.
- ✓ 6. An optical device as set forth in claim 4,
wherein an alignment layer for aligning the liquid
25 crystal in one direction is provided at the surface
of said transparent electrode on the side of the

layer including the variable refractive index material.

7. An optical device as set forth in claim 6,
5 wherein a light is incident to a surface of said layer including the variable refractive index material having a more uniform alignment.
- ✓ 8. An optical device comprising a plurality of
10 optical devices defined in claim 6, said plurality of optical devices being arranged in series so that the ordering directions of the respective alignment layers are perpendicular to each other.
- 15 9. An optical device as set forth in claim 1, wherein said two transparent electrodes are substantially parallel transparent electrodes.
10. An optical device as set forth in claim 1,
20 wherein the surface configuration of the transparent material layer on the side of said layer of the variable refractive index material is a convex lens, a concave lens, a fresnel lens, a prism array, a lens array, a lenticular lens or a diffraction
25 grating, or a curved surface formed by a combination thereof.

- ✓ 11. An optical device as set forth in claim 1,
wherein one of said transparent electrodes is
replaced with an electrode reflecting at least a
part of a light incident to said one of said
5 transparent electrodes.

12. An optical device comprising:

a layer including a variable refractive index
material having dielectric constant anisotropy and
10 having a property to reverse signs of a difference
of dielectric constant $\Delta\epsilon$ due to anisotropy at
driving frequencies f_1 and f_2 ;

at least two transparent electrodes arranged to
sandwich said layer including said variable
15 refractive index material; and

a driving device applying a voltage, in which
voltages from V_1 to V_N respectively having
respective primary frequencies f_1 to f_N ($N \geq 2$) are
superimposed, between said transparent electrodes.

20

- ✓ 13. An optical device as set forth in claim 12,
wherein a transparent material layer having desired
curved surface configuration is disposed between
said at least two transparent electrodes and
25 adjacent said layer including said variable
refractive index material.

- ✓ 14. An optical device as set forth in claim 13,
wherein one of said transparent electrodes is
replaced with an electrode reflecting at least a
part of a light incident to said one of said
5 transparent electrodes.
15. An optical device as set forth in claim 12,
wherein when applying a voltage in which voltages V_1
to V_N having respective primary frequencies f_1 to f_N
10 ($N \geq 2$) are superimposed, said driving device
temporarily suspends the supply of the voltage at a
desired timing and subsequently resume the supply of
the voltage.
- 15 16. An optical device as set forth in claim 12,
wherein a dual-frequency liquid crystal is employed
as said variable refractive index material having
the refractive index anisotropy and the dielectric
constant anisotropy and having a difference $\Delta\epsilon$ of the
20 different dielectric constant which is reversed at
the driving frequencies f_1 and f_2 .
- ✓ 17. An optical device as set forth in claim 16,
wherein a material having a low wettability with the
25 liquid crystal is arranged at least one of positions
contacting said layer of the liquid crystal.

✓ 18. An optical device as set forth in claim 16,
wherein an alignment layer for aligning the liquid
crystal in one direction is provided on the surface
5 of said transparent electrode on the side of the
layer including the variable refractive index
material.

19. An optical device as set forth in claim 18,
10 wherein a light is incident to a surface of said
layer including the variable refractive index
material having a more uniform alignment.

✓ 20. An optical device comprising a plurality of
15 optical devices defined in claim 18, said plurality
of optical devices being arranged in series so that
the ordering directions of the respective alignment
layers are perpendicular to each other.

20 21. An optical device as set forth in claim 12,
wherein said two transparent electrodes are
substantially parallel transparent electrodes.

22. An optical device as set forth in claim 12,
25 wherein the surface configuration of the transparent
material layer on the side of said layer of the

variable refractive index material is a convex lens,
a concave lens, a fresnel lens, a prism array, a
lens array, a lenticular lens or a diffraction
grating, or a curved surface formed by a combination
5 thereof.

23. An optical device comprising:

a layer of transparent material having a desired
curved surface configuration;

10 a layer including a variable refractive index
material having a positive or negative dielectric
constant anisotropy;

at least two transparent electrodes arranged to
sandwich said layer of the transparent material and
15 said layer including the variable refractive index
material; and

a driving device for always supplying a voltage
substantially equal to or greater than an amplitude
of a voltage establishing static and vertical
20 alignment in said variable refractive index
material.

24. An optical device as set forth in claim 23,
wherein said voltage from said driving device is an
25 AC voltage having a primary frequency in a range of
1 Hz to 100 Hz.

25. An optical device as set forth in claim 23,
wherein said variable refractive index material is
nematic liquid crystal.

5 26. An optical device as set forth in claim 23,
wherein said at least two transparent electrodes are
substantially in parallel.

27. An optical device as set forth in claim 23,
10 wherein the surface configuration of the transparent
material layer on the side of said layer of the
variable refractive index material is a convex lens,
a concave lens, a fresnel lens, a prism array, a
lens array, a lenticular lens or a diffraction
15 grating, or a curved surface formed by a combination
thereof.

28. An optical device as set forth in claim 23,
wherein an alignment layer for aligning the liquid
20 crystal in one direction is provided on the surface
of said transparent electrode on the side of the
layer including the variable refractive index
material.

25 29. An optical device comprising a plurality of
optical devices defined in claim 28, said plurality

of optical devices being arranged in series so that the ordering directions of the respective alignment layers are perpendicular to each other.

5 30. An optical device as set forth in claim 23, wherein a light is incident to a surface of said layer including the variable refractive index material having a more uniform alignment.

10 31. An optical device as set forth in claim 23, wherein one of said transparent electrodes is replaced with an electrode reflecting at least a part of a light incident to said one of said transparent electrodes.

15

32. A three-dimensional display device for forming three dimensional image from two-dimensional image on a display portion, comprising:

20 a layer of a transparent material having a decided curved surface configuration;

a layer of a variable refractive index material having a refractive index varying in accordance with a voltage applied thereto;

25 at least two transparent electrodes arranged to sandwich said layer of the transparent material and

said layer including the variable refractive index material;

an imaging position shifting portion for shifting an imaging position of said two-dimensional image displayed on said display portion;

5 a synchronizing portion for synchronizing an updating period of the two dimensional image displayed on said display portion with a shifting period of the imaging point of said imaging position shifting portion; and

10 a driving portion for driving said imaging point shifting portion by applying a voltage to said at least two transparent electrodes in accordance with an output from said synchronizing portion.

15

33. A three-dimensional display device as set forth in claim 32, wherein said variable refractive index material of said imaging point shifting portion is liquid crystal.

20

34. A three-dimensional display device as set forth in claim 33, wherein a material having a low wettability with the liquid crystal is arranged at least one of positions contacting said layer of the liquid crystal of said imaging point shifting portion.

25

35. A three-dimensional display device comprising a plurality of optical devices defined in claim 34, said plurality of optical devices being arranged in series so that the ordering directions of the
5 respective alignment layers are perpendicular to each other.

36. A three-dimensional display device as set forth in claim 33, wherein an alignment layer for aligning
10 the liquid crystal in one direction is provided on the surface of said transparent electrode on the side of the layer including the variable refractive index material of said imaging point shifting portion.

15

37. A three-dimensional display device as set forth in claim 36, wherein a light is incident to a surface of said layer including the variable refractive index material having a more uniform
20 alignment.

25

38. A three-dimensional display device as set forth in claim 32, wherein said two transparent electrodes are substantially in parallel.

39. A three-dimensional display device as set forth in claim 32, wherein said display portion displays depth sampling images formed by decomposing a three-dimensional image into two-dimensional images
5 between planes set at a predetermined interval in a depth direction of an image pick-up position, or depicts a line drawing.

40. A driving method of driving a three-dimensional
10 display device including a display portion for displaying two-dimensional images, an imaging point shifting portion disposed between said display portion and an observer, a synchronizing portion for synchronizing an updating period of the two-
15 dimensional images displayed on said display portion with a shifting period of the imaging point of said imaging point shifting portion, and a driving portion for driving said imaging point shifting portion, said a driving method comprising the steps
20 of:

outputting a plurality of driving signals of an output voltage V_N ($N \geq 2$) having frequency f_N as a primary frequency for a predetermined period of time assigned to each of the driving signals in a
25 predetermined sequence to drive said imaging point shifting portion in said driving portion; and

updating and displaying said two-dimensional images in a predetermined sequence on said display portion in said synchronizing portion.

- 5 41. A driving method of driving a three-dimensional display device including a display portion for displaying two-dimensional images, an imaging point shifting portion disposed between said display portion and an observer, a synchronizing portion for
10 synchronizing an updating period of the two-dimensional images displayed on said display portion with a shifting period of the imaging point of said imaging point shifting portion, and a driving portion for driving said imaging point shifting
15 portion, said a driving method comprising the steps of:

in said driving portion:

- generating a driving signal of a predetermined output voltage in which a frequency ΩN ($N \geq 2$) is
20 superimposed;

applying said driving signal to said imaging position shifting portion;

- varying said output voltage in a predetermined sequence in accordance with a synchronization signal
25 of said synchronizing portion; and
in said synchronization portion:

outputting a synchronization signal in said synchronization portion when updating two-dimensional images to be displayed on said display portion.

5

42. A driving method as set forth in claim 40, further comprising a step of stopping said driving signal for driving said imaging point shifting portion driving a predetermined time duration.

10

43. A driving method as set forth in claim 41, further comprising a step of stopping said driving signal for driving said imaging point shifting portion driving a predetermined time duration.

15

44. A three-dimensional display device comprising:
a phantom three-dimensional display device for displaying a phantom three-dimensional image; and
a shutter device formed by a shutter element for
controlling a light transmittance, said shutter
device being located at a position where said
phantom three-dimensional image is reproduced or a
position optically equivalent to said position.

20 45. A three-dimensional display device as set forth in claim 44, wherein said shutter element is two-

dimensionally divided, and each of divided regions are driven independently of the other.

46. A three-dimensional display device as set forth
5 in claim 44, wherein said shutter element lowers a light transmittance in the region of depth sampling images as two-dimensional images of said phantom image at said shutter element position during a time duration that said phantom three-dimensional image
10 is being reproduced on the other side of said shutter element as viewed from the observer.

47. A three-dimensional display device as set forth
in claim 44, wherein the material of said shutter
15 element is one or combination of guest-host type liquid crystal containing diachronic dye having a different light beam absorption depending upon an orientation of molecules and liquid crystal having dielectric constant anisotropy, polymer dispersion
20 type liquid crystal containing droplet-like liquid crystal in polymer, polymer dispersed liquid crystal containing a polymer network in liquid crystal, a holographic polymer dispersed liquid crystal having a layer structure of polymer dispersed liquid
25 crystal containing droplet like liquid crystal in polymer and polymer, a holographic polymer dispersed

liquid crystal having a layer structure of said
polymer dispersed liquid crystal containing a
polymer network in the liquid crystal and polymer,
and a polymer dispersed liquid crystal wherein said
5 liquid crystal in said polymer dispersed liquid
crystal is said guest-host type liquid crystal.

48. A three-dimensional display device as set forth
in claim 44, wherein said phantom three-dimensional
10 display device is constructed with a two-dimensional
image display device and a varifocal optical device.

49. A three-dimensional display device comprising:
a phantom three-dimensional display device for
15 displaying a phantom three-dimensional image; and
a shutter device formed by a shutter element for
controlling a light transmittance,

said phantom three-dimensional image being a
real image, and said shutter element being a
20 photoreactive element for lowering a light
transmittance in a real image region at the position
of said shutter element in accordance with an
imaging light beam of said real image.

25 50. A three-dimensional display device as set forth
in claim 49, wherein a material of said

photoreactive element is one of a photochromic material, a material consisting of a material causing a photostructural change and liquid crystal, and a material having a nematic-anisotropic phase transition temperature to be varied by photostructural change.

51. A three-dimensional display device as set forth in claim 49, wherein said phantom three-dimensional display device includes a two-dimensional image display device and a varifocal optical device.

52. A head-mount display device comprising:
two display devices corresponding to left and right eyes and each including a two-dimensional display device and an optical device having a variable focal length; and

a control device for controlling said two dimensional display device and said optical device having a variable focal length,

said display devices being mounted to left and right eyes, and said control device synchronously driving said two-dimensional display device and said optical device to perform three-dimensional display.

25

53. A head-mount display device as set forth in claim 52, wherein said optical device further comprises a deflection device for varying a direction of a light incident to said optical device, and said control device controls said optical device in such a way that when the image is moving closer to the eyes according to a change of the focal length, the overall display image of said two-dimensional display device is deflected to be closer toward the center between the left and right eyes.

54. A head-mount display device as set forth in claim 52, wherein said optical device has a transparent material of one of forms of a fixed focus lens shape, a fixed prism shape, and a shape where the fixed deflection mechanism is incorporated into the fixed focus lens or a combination thereof, a layer including a variable refractive index material, and at least a pair of transparent electrodes for sandwiching said layer.

55. A head-mount display device as set forth in claim 54, wherein said variable refractive index material is liquid crystal having dielectric constant anisotropy and refractive index anisotropy.

56. A head-mount display device as set forth in claim 55, wherein said variable refractive index material is liquid crystal having dielectric constant anisotropy and refractive index anisotropy, and being dual-frequency liquid crystal having a different physical property having a different sign of a difference in a dielectric constant corresponding to orientation of the liquid crystal molecules between different frequencies f1 and f2.

10

57. A head-mount display device as set forth in claim 54, wherein said variable refractive index material is polymer dispersed liquid crystal, and the droplet size of the liquid crystal or the droplet size of the polymer is smaller than a wavelength of visible light.

15

58. A head-mount display device as set forth in claim 54, wherein said fixed focus lens is spherical or non-spherical single lens or fresnel lens.

20

59. A head-mount display device as set forth in claim 54, wherein said fixed prism is simple prism or a multi-prism having an array of a plurality of fine prisms.

25

60. A head-mount display device as set forth in claim 54, the form where said fixed deflection mechanism is incorporated in to said fixed focus lens is in the form of increasing or decreasing an angle formed by a spherical or non-spherical simple lens or a fresnel lens and an optical axis.

61. A head-mount display device as set forth in claim 52, wherein said driving device sequentially applies voltages V_1 to V_N having primary frequencies f_1 to f_N ($N \geq 2$) to said transparent electrodes for a predetermined period of time and at a predetermined interval.

ABSTRACT OF THE DISCLOSURE

An optical device includes a transparent material layer having a desired curved surface configuration, a layer including a variable refractive index material having a dielectric constant anisotropy, ~~and having a property in which a sign of a difference $\Delta\epsilon$ in dielectric constant due to the anisotropy is reversed at driving frequencies f_1 and f_2~~ , at least two transparent electrodes arranged to sandwich the transparent material layer and the ~~layer including the variable refractive index material~~, and a driving device supplying a voltage including ~~the~~ driving frequencies f_1 and f_2 between the transparent electrodes. *The difference $\Delta\epsilon$ in the dielectric constant of the variable refractive index material due to the anisotropy is positive at one of the driving frequencies and negative at the other driving frequency*